

WWH660 WCS TDos&WiFiConn@ct

W1 Front-loading washing machine  
with TwinDos, CapDosing, and WiFiConn@ct.



- Two-phase automatic detergent dispensing system - TwinDos
- Ironing made simple thanks to pre-ironing
- Portioned capsules for special laundry needs – Capsule dispensing
- Wash small & large loads efficiently- Automatic load recognition
- ENERGY STAR® qualified

EAN: 4002515830451 / material number: 10666180

<b>Construction type</b>	
Stackable	•
Side-by-Side	•
Slot-in	•
Door hinging	left
<b>Construction type</b>	
Product brand	W1 White Edition
Front loaders	•
<b>Spin</b>	
Rinse hold	•
Without spin" function	•
<b>Design</b>	
Appliance color	Lotus white
Control panel color	Lotus white
Door design	Lotus white with chrome ring
Rotary selector color	Lotus White / Chrome ring
Fascia panel version	5° incline
Control type	Rotary selector
Control panel	ComfortSensor white, 1 line
<b>Cleaning performance</b>	
TwinDos	•
CapDosing	•
<b>Gentle laundry care</b>	
Honeycomb drum	•
Load in lbs. (kg)	18 (8.0)
<b>Control panel</b>	
Delay start up to 24 h	•
Countdown indicator	•
Program sequence indicator	•
Drum lighting	LED
MultiLingua	•
AutoClean dispenser drawer	•
<b>Efficiency and sustainability</b>	
Hot water connection	•
EcoFeedback	•
Low-temperature washing "Cold" and "68°F"	•
Automatic load control	•
Flow meter	•
Foam control	•
ProfiEco motor	•

WWH660 WCS TDos&WiFiConn@ct

W1 Front-loading washing machine  
with TwinDos, CapDosing, and WiFiConn@ct.



<b>Wash programs</b>	
Delicates	•
Express	•
Outdoor	•
Proofing	•
Normal	•
Wrinkle-free	•
Sanitize	•
Handwash	•
Dress Shirts	•
Extra White	•
Darks/Denims	•
Table Linens/Drapes	•
Sportswear	•
Woolens	•
Silks	•
Drain/Spin	•
QuickRinse	•
Baby Clothes	•
Towels	•
Downs	•
Pillows	•
Care – Clean Machine	•
Care – Clean TwinDos	•
Settings – Anti-Crease	•
<b>Wash options</b>	
Soak	•
Pre-rinse	•
Pre-ironing	•
<b>Appliance networking</b>	
WiFiConn@ct	•
<b>Quality</b>	
Suds container	Stainless Steel
Counterweights made of cast iron	•
<b>Safety</b>	
Water Control System	•
Child Child lock	•
Lock code	•
Optical interface	•
<b>Technical data</b>	
Dimensions (width) in in.(mm)	23 1/2 (596)
Dimensions (height) in in.(mm)	33 1/2 (850)
Dimensions (depth) in in.(mm)	25 3/8 (643)
Depth with door open in in.(mm)	42 1/2 (1,077.0)
Weight in lbs. (kg)	212 (96.00)
Total connected load in kW	1.300
Fuse rating in A	15
Length of supply lead in feet (ft.)	6 (2)
<b>Standard accessories</b>	
3 capsules	•
UltraPhase 1+2	•