



36" Gas Ranges

Wolf has perfected the form, function and sheer durability of our gas ranges. Wolf gas ranges offer standard features such as an infrared oven broiler, convection baking, dual brass surface burners and our signature large red control knobs. Optional infrared charbroiler and infrared griddle give you the freedom to customize your gas range. Wolf gas ranges are available in natural or LP gas.



Model R364C shown.



Model R366



Model R364C



Model R364G

FEATURES

- Stainless steel exterior finish.
- Optional infrared charbroiler and infrared griddle configurations.
- Distinctive red control knobs with chrome bezels—black knobs optional.
- Dual brass burners with automatic reignition at all settings.
- Porcelain-coated cast iron grates.
- Large-capacity convection oven with infrared broiler and three adjustable oven racks.
- Spring/damper door hinge system.
- Stainless steel drip tray.
- Adjustable stainless steel legs in front and rear casters.
- Full side panels and skirt.

SURFACE FEATURES

Model	R366	R364C	R364G
Surface Burners 16,000 Btu high / 500 Btu simmer	6	4	4
Infrared Charbroiler—16,000 Btu		•	
Infrared Griddle—18,000 Btu			•

Model numbers are for natural gas ranges, add (-LP) to the model number for LP gas.

ACCESSORIES

- Stainless steel risers in 5" and 10", or 20" riser with shelf.
- Stainless steel island trim.
- Black control knobs.
- Porcelain-coated, cast iron wok grate.
- Porcelain-coated, cast iron two-burner S-grates.
- Oven rack.
- Full-extension ball bearing rack.
- Hardwood cutting board (griddle model only).
- Griddle cleaning kit.




This appliance is certified by Star-K to meet strict religious regulations in conjunction with specific instructions found on www.star-k.org.

Accessories are available through your authorized Wolf dealer. For local dealer information, visit the find a showroom section of our website, wolfappliance.com.



Infrared griddle.



Dual brass burner.



Exterior Finish	Stainless Steel
Overall Width	36"
Overall Height (to cooking surface)	37"
Overall Depth	28 ³ / ₈ "
Oven Interior Capacity	5.5 cu ft
Oven Interior Dimensions	30" W x 18 ⁵ / ₈ " H x 17" D
Opening Width	36 ¹ / ₄ "
Opening Height (to countertop)	36"
Opening Depth	24"
Electrical Requirements	110/120 V AC 50/60 Hz, 15 amp circuit
Shipping Weight	445–470 lbs

- A riser is required for installations against a combustible surface.
- A Wolf pro wall, chimney, island ventilation hood or hood liner is recommended.

[illegible]

Unit dimensions may vary by $\pm 1/8"$.

Diagram illustrating the layout and dimensions for a cooktop and oven installation, showing clearances and opening widths.

Dimensions and Clearances:

- Top Clearance:** 30" (762) TO 36" (914) TO BOTTOM OF VENTILATION HOOD**
- Side Clearance:** 6" (152) TO COMBUSTIBLE*
- Opening Width:** 36 1/4" (921)
- Bottom Clearance (Left):** 10" (254) and 5 3/4" (146) to the oven cutout.
- Oven Cutout:** 12" (305) wide, 20 1/4" (518) high.
- Bottom Clearance (Right):** 7 3/4" (197) to the oven cutout.
- Countertop Clearance:** 18" (457) min. from the floor to the countertop.
- Countertop to Cooking Surface:** 36" (914) FLOOR TO COUNTERTOP and 37" (940) TO COOKING SURFACE.
- Side Cabinet Clearance:** 13" (330) max.
- Gas and Electrical:** LOCATION OF GAS AND ELECTRICAL EXTENDS ON FLOOR.
- Bottom Clearance (Right):** 3" (76) to the floor.

**Minimum clearance from rough opening to combustible materials up to 18" (457) above countertop.*

****36" (914) minimum clearance, 44" (1118) for charbroiler, from countertop to combustible materials without ventilation hood.**

NOTE: For island installations, 12" (305) minimum clearance from back of range to combustible rear wall above countertop.

Dimensions in parentheses are in millimeters unless otherwise specified.