

NOVA53PDC



45.5" x 60.75" x 27.25" (H x W x D)

61" wide fully assembled commercial dipping cabinet made in Europe with digital thermostat, sneezeguard, and light

Highlights:

Fully assembled dipping cabinet with durable polycarbonate sneezeguard and light

Digital thermostat for easy temperature control, with a wide range between -13 and 23°F to accommodate ice cream, gelato, and other frozen treats

Tub holder baskets for convenient ice cream storage

Product Features:

Commercially listed	UL-S listed to NSF-7 Standards for use in commercial establishments
Digital thermostat	Electronic controls for precise temperature management
Wide temperature range	Digital thermostat can be set between -13 and +23°F to accommodate a variety of frozen treats
Sneezeguard	Durable polycarbonate sneezeguard is pre-installed
Ice cream tub holders	Five epoxy coated wire baskets with plastic lids included to hold standard ice cream tubs in place
Holds 18 standard 3 gallon tubs	Unit can store 8 tubs on the floor and display an additional 10 using the provided baskets
Strong insulation	3" thick insulation helps to ensure items stay cold
Casters	Heavy duty wheels for smooth mobility (ship unassembled)
Sliding glass lid	Two tempered glass lids on ball-bearing glides slide open and closed easily for added efficiency

NOVA53PDC Specifications:

Overview	
Height of Cabinet	45.5" (116 cm)
Width	60.75" (154 cm)
Depth	27.25" (69 cm)
Capacity	17.8 cu.ft. (504 L)
Defrost Type	Manual
Door	Glass
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	UL-S
Amps	4.2
Voltage/Frequency	115 V AC/60 Hz
Weight	190.0 lbs. (86 kg)
Shipping Weight	210.0 lbs. (95 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101060187
Freezer	
Door Swing	Sliding
Interior Height	26.0" (66 cm)
Interior Width	54.5" (138 cm)
Interior Depth	21.0" (53 cm)
Thermostat Type	Digital
Refrigerant Type	R290a
Refrigerant Amount	3.17 oz.
High Side PSI	345.0
Low Side PSI	140.0
Wheels	4
Compressor Step Height	9.75" (25 cm)
Compressor Step Width	7.88" (20 cm)
Compressor Step Depth	21.0" (53 cm)
Temperature Range	-13 to 23°F

