

SPECIFICATION SHEET

CP47I SERIES RANGE HOODS

All-in-one design includes liner, blower, filtration, controls, lighting, and damper for easy installation into custom canopy hoods. Intended for all residential applications, including commercial-style cooking surfaces.

FEATURES

- Cabinet mount custom applications
- Finish: 430 Stainless Steel #4 Brushed
- Width: 34-3/8, 40-3/8, 46-3/8, 52-3/8, 58-3/8, 64-3/8
- Depth: 22-1/2"
- 10" round duct connector with backdraft damper
- Four-setting cooktop lighting (Uses 50W, GU10 halogen lamps. Bulbs included. 2 lamps on 34-3/8" wide hood, 4 lamps on all other hood widths.)
- Easily accessible, dishwasher safe stainless steel Evolution[™] baffle filters with handles
- 4-speed electronic blower control with LinkLogic[®] enabled technology
- Powerful, centrifugal blower with high-efficiency motor produces 1000-1110 CFM
- Quiet operation
- Heat $\mathsf{Sentry}^{\mathsf{TM}}$ automatically turns blower to high speed when • excess cooking heat is detected
- Delay timer control automatically shuts off range hood after 10 minutes
- Special control indicates when it's time to clean the filter

SPECIFICATIONS

MODEL NO.	VOLTS	AMPS	CFM / SONES (High Speed)	CFM / SONES (Low Speed)	DUCT
CP47I362SB	120	6.5	1000 / 12.0	370 / 1.5	10" round
CP47I422SB	120	7.0	1000 / 12.0	370 / 1.5	10" round
CP47I482SB	120	7.0	1080 / 10.5	410 / 1.5	10" round
CP47I542SB	120	7.0	1110 / 10.5	420 / 1.5	10" round
CP47I602SB	120	7.0	1110 / 10.5	420 / 1.5	10" round
CP47I662SB	120	7.0	1110 / 10.5	420 / 1.5	10" round

*34-3/8", *40-3/8", *46-3/8" *22-1/2

001

HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to

on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

* Add 1/16"

for rivet heads.

'3'

Best Hartford, Wisconsin www.BestRangeHoods.com 800-558-1711 Best Mississauga, Ontario www.BestRangeHoods.com 877-896-1119

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by Date

OPTIONS

ึ่

5:11%

Non-ducted kit

- ANKCP4742 (40-3/8" width only)

ANKCP4748 (46-3/8" width only)
ANKCP4760 (58-3/8" width only)

- AFCCP4748 (46-3/8" width only)

- AFCCP4760 (58-3/8" width only)

- Charcoal filters included

 Replacement charcoal filters: - AFCCP4742 (40-3/8" width only)

Ç

*52-3/8", *58-3/8", *64-3/8"

CP47I SERIES HOOD SYSTEM



