



Technical drawing of a kitchen cabinet showing dimensions and a cutaway view of the base.

Dimensions:


- Top width: 25"
- Top depth: 23.25"ⁿ⁴
- Front height: 36"
- Base cutaway width segments: 5 1/2", 19", 5 1/2"
- Base cutaway height segments: 10", 2 1/4"
- Base cutaway depth: 24"
- Base cutaway total width: 30"

Labels:

- GAS AND ELECTRIC SUPPLY LOCATION
- 6

MODEL SKUs

AGS1740BDQ



Style of product may vary from picture

1. Depth excluding handle. Dimension given is from wall to front of oven door.
2. Height may vary slightly depending upon leveling legs.
3. If cabinet backsplash behind unit is not present, backsplash kit (UXA9107AA in B=black, W= white, Q= bisque, S=stainless) may be ordered from dealer.
4. When replacing an existing unit, a maximum of 23 1/2" is acceptable. If the cut depth exceeds 23 1/2" use filler kit (K71FILL in B=black, W= white, Q=bisque).
5. If end cabinet is not present, side panel kit (UXA1100AA in B=black, Q=bisque, W=white, S=stainless) may be ordered from dealer.
6. 120 Volt Grounded Electrical Outlet in the hatched area. Outlet MUST be flush. Nothing located in hatched area can extend more than 2" from wall or range will not slide all the way back.
7. Some white European style cabinets are equipped with delicate white vinyl drawer and door fronts. The vinyl may not be designed to withstand the heat produced by the normal safe operation of a selfclean range. Discoloration or delamination may occur. To avoid possible damage, we recommend increasing the 30" cabinet opening to 31 1/4" minimum and using heat shield (CABKIT V). The countertop cut-out must remain 30". Gas lines MUST be installed within the dark shaded and hatched area to ensure proper alignment of this oven with your cabinets. It is recommended to have gas and electric supplies 6" apart.

2005-09-07 at 15:19:26 CDT