



Hotpoint® PTAC Heat Pump Unit with Electric Heat 12,000 BTU, 20 amps, 265 Volt

Model# AH11H12E3B



- 3-speed fan - Give guests control over their comfort with three fan speeds to choose from
- 4-temperature limiting options - Easily select one of four temperature ranges for peak efficiency and total customer comfort
- Freeze and frost protection - Automatic freeze and indoor frost control keep units operating in peak condition
- Auto power recovery - In case of power failures, units automatically resume their operation when power restores, reducing maintenance calls
- Self diagnostics - Quickly and easily identify service needs with a nine-point diagnostic code system
- Automatic emergency heat - Keep guests comfortable with a heating option that uses electric resistance heat in heat pump mode
- Backed by an industry leader - With a long history of creating durable products at an affordable price, Hotpoint is your trusted PTAC brand
- Limited 1-year parts and labor entire appliance warranty / limited 5-year refrigerating system warranty - Enjoy peace of mind knowing that all purchases are backed by the trusted Hotpoint service network
- Intuitive display - Allow guests to easily customize their preferred settings and reduce maintenance calls with an easy-to-use control panel
- Power cord (LCDI) included - Hotpoint PTACs come with everything needed for a quick and easy installation

FEATURES

| | |
|-------------------------------|--|
| Control Type | Electronic |
| Fan Speed Selections | 3 Cooling 3 Fan Only 3 Heating |
| Discharge Grille | 2-position |
| Product Type | Packaged Terminal Air Conditioners (PTAC) |
| Refrigerant Type | R410A |
| Manual Vent Control | Hidden |
| "SmartFan" Fan Cycle | Yes |
| Chassis Type | Slide-In |
| Fan Motor | 2 |
| Heat Pump | Yes |
| Unit Features | Auto Power Recovery Automatic Emergency Heat Automatic Indoor Frost Control Central Desk Control Compatibility Freeze Sentinel Heat Pump with Resistance Heat Backup Power Cord included Remote Thermostat Compatibility Sub-Base required |
| Temperature Range | 62 - 86 F |
| Heat - Cool | Yes |
| Auto Power Recovery | Yes |
| Rotary Compressor | Yes |
| Heating - Reverse Cycle - COP | 3.2 |
| Outdoor Vent / Exhaust | Yes |
| Venting Features | Concealed Manual Vent Control Air Filter |
| Heating System | Heat Pump with Resistance Backup |

- Remote thermostat compatibility
- Works with central desk control systems
- Heatpump models include staged heating
- Tangential fan for air flow and smooth sound
- Energy-efficient heat pump models available

Have more questions? Please contact 1-800-626-2000



GE APPLIANCES
a Haier company

CustomerNet

Hotpoint® PTAC Heat Pump Unit with Electric Heat 12,000 BTU, 20 amps,
265 Volt

Model# AH11H12E3B

APPROXIMATE DIMENSIONS(HxDxW)

- 16 H x 42 W x 21 D

CAPACITY

- Cooling BTUH (MAX) - 12000.00Btu
- CFM Indoor Fan Low - 310
- CFM Indoor Fan Medium - 349
- CFM Indoor Fan High - 383
- Cooling EER (BTUH / Watt) - 10.5
- Heating - Reverse Cycle - BTUH - 10800
- Cooling BTUH (MIN) - 11800Btu

APPEARANCE

- Installation - Through-the-Wall
- Color Appearance - White

WEIGHTS & DIMENSIONS

- Overall Width (in) - 42in
- Approximate Shipping Weight (lb) - 126 4/5lb
- Overall Height (in) - 16in
- Overall Depth (in) - 21in
- Net Weight (lb) - 113 1/10lb

POWER / RATINGS

- Heating - Reverse Cycle - Watts - 989
- Cooling - Amperes - 4.31
- Cooling - Watts - 1142
- Heating - Reverse Cycle - Amps - 4.3
- Heating - Electric - Heater Watts - 3535/2935
- Voltage (MAX) - 265.000000V
- Heating - Electric - Heater Amps - 13.46

WARRANTY

- Warranty Notes - See written warranty for full details
- Labor Warranty - Limited 1-year entire appliance
Limited 5-year sealed refrigerating system
- Parts Warranty - Limited 1-year entire appliance
Limited 5-year sealed refrigerating system

CERTIFICATIONS

- Claims & Certifications - AHRI
UL
CUL

Have more questions? Please contact 1-800-626-2000