| ٨ | D | \sim |
|---|---|--------|
| А | Γ | C |



WALL

The Wave looks great with any number of décor styles, from transitional to modern, and the elegant tilt lends a slim profile to this kitchen workhorse. An ingenious dual capture zone ensures a smoke and debris-free kitchen.

Offering a glowing tri-level LED light strip, and a choice of black or white glass and an optional duct cover, the Wave is a true kitchen classic.



MODEL

| White Glass w/ Stainless Steel | AWA-M90AWX | | | |
|-------------------------------------|----------------------|--|--|--|
| Black Glass w/ Stainless Steel | AWA-M90ABX | | | |
| Size | 90cm (35-7/16″) | | | |
| Internal Blower CFM* | 290, CBI-290A | | | |
| Internal Blower CFM* | 600, CBI-600A | | | |
| In-line Blower CFM* | 1,000, PBN-1000A | | | |
| External Blower CFM* | 1,000, CBE-1000 | | | |
| Max. Sones | 3.2-6 | | | |
| Controls | Capacitive Touch | | | |
| Speed Levels | 3 | | | |
| Auto Delay-Off | Yes | | | |
| CleanAir Function** | Yes | | | |
| Lighting | LED Strip x 1 (8.5W) | | | |
| Tri-Level Lighting | Yes | | | |
| Filters | Aluminum Mesh x1 | | | |
| Wireless Remote Control | Yes, RF | | | |
| Recirculating | Yes | | | |
| Optional Duct Cover | Yes | | | |
| DUCT SPECIFICATIONS | | | | |
| Vertical/Horizontal Internal Blower | 6″ | | | |
| Vertical In-Line/External Blower | r 10" to 8"*** | | | |
| Horizontal In-Line/External Blower | 10" to 8"*** | | | |
| AC INPUT | 120V - 60Hz | | | |
| AC POWER**** | Max. 0.2 Amps | | | |
| OPTIONAL ACCESSORIES | | | | |
| Recirculating Kit | ZRC-00WA | | | |
| Duct Cover | Z1C-00IN | | | |
| Make-Up Air Kit | MUA006A (600 CFM) | | | |
| | MUA008A (1,000 CFM) | | | |
| MOUNTING HEIGHT RANGE [†] | 22" - 32" | | | |

WARRANTY

1 Year parts, 1 year labor

HOOD HEIGHT CALCULATOR - With Duct Cover

| CEILING HEIGHT | 8′ | 8.5′ | 9' | 9.5′ | 10′ | 10.5′ | 11′ | 12′ |
|----------------|----|------|-------------|-----------|-----------|-------|-----|-----|
| | NA | NA | 22″ - 27.5″ | 22″ - 32″ | 28″ - 32″ | NA | NA | NA |

*Blower sold separately.

CleanAir turns your hood on once every four hours for 10 minutes on speed one. **ToleanAir turns your hood on once every four hours for 10 minutes on speed one. *10" round duct connects to external and in-line blower. Must transition from 10" to 8" before duct passes through ceiling. A 10" to 8" adapter is included with external and in-line blowers. ****AC power listed above is for hood with lights only. For blower specifications please refer to the blower spec sheet. *Mounting height refers to distance between top of a 36" tall cooking surface and bottom of hood.



| ARC |
|------|
| WAVE |

WALL



