QUICK REFERENCE GUIDE > BE1-48C-N Date: 19.03.2025 > 1

48" Series 9 Grill, Charcoal, Natural Gas

Series 9

Stainless Steel | Natural Gas



This Series 9 Built in 48" Grill provides the ultimate grilling space for premium outdoor kitchens and will take your grilling experience to the next level.

- Secondary cooking surface allows you to use a wide repertoire of cooking styles and cater for a crowd
- Intuitive lighting with bright in-hood lights and bezel lit control dials
- Easy to lift 90° hood for better access when cooking
- Delivers 25,000 BTU/hr total power per burner allowing you to precisely control heat from 300°F to 1100°F

DIMENSIONS

Height	27 1/4 "
Width	47 15/16 "
Depth	26 7/8 "

FEATURES & BENEFITS

Easy Lifting Hood

With extra space under the hood for extra large food items, the hood can be smoothly opened, using one hand, to a full 90° for better access and visibility when cooking.

Storage For Racks And Tools

The 6" storage accessory extends your grill to fit a 42" or 54" space. It bolts seamlessly onto either side of the grill to store racks, grates and tools. This accessory is sold separately.

SPECIFICATIONS

Accessories (sold separately)

6" accessory storage	ASE6-48
Built-in grill cover	ACBI-48E
Griddle plate	BGC-GP TEST
Insulated jacket	BGA48-IJS (optional)
Insulated jacket (with storage accessory unit)	BGA54-IJS (optional)
On cart grill cover	ACC-48E
Optional cart mount	CAD-48E

Burners

Number of U-burners

Cooking Surface Area

Primary cooking area	855 sq.in.
Secondary cooking area	738 sq.in.
Total cooking area	1593 sq.in.

Features

flat and angled position	Double sided grilling grates
•	Full charcoal burner/smoker
•	Full surface searing
•	Grease management system™
•	Hood temperature gauge
Hot surface	Ignition system
•	Metal dials
2-level racks and tray	Secondary cooking features

Finish

304 grade	Material
stainless stee	
	Weather resistant

Gas Requirements

1/2" NPT male	•
Gas type	NG



QUICK REFERENCE GUIDE > BE1-48C-N Date: 19.03.2025 > 2

T 1.888.936.7872 Wwww.dcsappliances.com

Operational pressure	4" W.C.	↓ Installation Guide Grill EN
Supply pressure	6" to 9" W.C.	→ Guide d'installation FR
Installation Biocomicon		Planning Guide EN - Professional Grills Series 9 Outdoor Kitchen
Installation Dimensions		Service and Warranty
Cutout depth (proud)	22 3/4 "	↓ User Guide Grill EN
Cutout height (proud)	10 1/8 "	Guide d'utilisation FR
Cutout width (proud)	45 3/4 "	→ Guía del usuario SP
Insulated jacket for proud cut-out	Varies - check manual	A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

100000 BTU

25000 BTU

Power Requirements

Performance
Total Power

U-burner power

Supply frequency	60
Supply voltage	120 V

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

Other product downloads available at dcsappliances.com