

BIM44G



33" x 14.5" x 23.5" (H x W x D)

15" wide built-in undercounter NSF-listed clear icemaker with automatic defrost and internal pump

Highlights:

- Commercial ENERGY STAR certification
- Flexible design allows built-in or freestanding use
- Automatic defrost saves on user maintenance

Product Features:

ENERGY STAR certified commercial performance	Efficient performance for commercial use
Commercially approved	NSF listed for use in commercial establishments
Built-in pump	Internal pump allows more flexibility in placing the unit
Reversible door	Keep your options flexible with a reversible door that is easy to switch when your arrangement changes; Unit ships LHD but can be reversed in our factory or by the user
Automatic defrost	Reduced maintenance with auto defrost system
Built-in capable	Make the best use of space by installing your icemaker under the counter
Stainless steel door	Professional styling with lasting durability
Professional towel bar handle	A curved handle in brushed stainless steel offers an easy grip
Clear ice cube production	Makes cubes sized at 3/4" x 3/4" x 1"

BIM44G Specifications:

Overview	
Height of Cabinet	33.0" (84 cm)
Width	14.5" (37 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.0" (64 cm)
Depth with door at 90°	37.0" (94 cm)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	NSF
Amps	4.8
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Shipping Weight	105.0 lbs. (48 kg)
Estimated Time to Ship	Next day shipping
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Ice maker	
Door Swing	LHD
Reversible	Yes
Drain Required	Yes
Daily Ice Production	50.0 lbs. (23 kg)
Ice Storage Capacity	25.0 lbs. (11 kg)
Ice Shape	Cube
Size of Cube	3/4" x 3/4" x 1"
Number of Ice Cube Sizes	1
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	3.88 oz.
High Side PSI	350.0
Low Side PSI	130.0
Interior Height	18.5" (47 cm)
Interior Width	12.0" (30 cm)
Interior Depth	16.0" (41 cm)
Level Legs	4

