



Color Variants

BX480612
Stainless steel-backed full glass door
Width 30" (76 cm)

Included accessories

1 x enamel baking tray, suit. pyrolytic clean.
1 x rotary spit.
1 x grill shelf.
1 x grill tub with grid.
1 x pluggable meat probe.

Optional accessories

BA018165
Pull-out system
BA028115
Baking tray, enameled
BA038165
Wire rack, chromium-plated
BA058115
Heating element for baking stone and cast-iron roaster
BA058133
Baking stone
BS020002
Pizza peel, additional set of 2
GN340230
Non-stick aluminum cast-iron roaster

Product Variants

BX481612
400 series double oven
Stainless steel-backed full glass door
Width 30" (76 cm)
left-hinged
Controls centered

BX480612
400 series double oven
Stainless steel-backed full glass door
Width 30" (76 cm)
right-hinged
Controls centered

Pyrolytic self-cleaning system
Universal heating system with 17 heating methods, with core temperature probe, rotisserie spit and baking stone operation
Core temperature probe with estimation of cooking time
TFT touch display
Electronic temperature control from 85°F - 550°F
2x 4.5 cu.ft. (110 litres) net volume.

Cooking modes

Convection.
Economy convection..
Top + bottom heat.
Top + 1/3 bottom heat.
Top heat.
1/3 top + bottom heat.
Bottom heat.
Convection + bottom heat.
Convection + 1/3 bottom heat.
Convection broiling..
Broiling.
Compact grill.
Baking stone operation.
Roaster function.
Dough proofing.
Defrosting.
Keeping warm.

Operation

Rotary knob and TFT touch display operation.
Clear text display in 25 languages.
Information key with use indicators.
Side-opening door opens up to 180° angle.

Features

Three-point core temperature prove with automatic shut-off and estimation of cooking time.
Rotisserie spit (lower oven).
Baking stone outlet.
Actual temperature display.
Fast heating setting.
Timer functions: cooking time, switch-off time, short-term timer, stopwatch.
60 W halogen light on the top.
10 W halogen light on the side.
Enamelled side shelf supports with 5 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quadruple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Pyrolytic self-cleaning.
Gaggenau Clean-Enamel.
Heated air cleaning catalyst.

Planning notes

Door hinge not reversible.
The front of the appliance extends 1 7/8" from the cabinet front.
Consider the overhang when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the 90° door opening angle.
To achieve the 21 5/8" installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing.
Plan a power outlet outside of the cut-out niche.

Product Features

Cooking mode

Baking stone function, Bottom heat, Bottom heating, 1/3 top heat., Conventional heat, Defrost, Dough proving setting, Full width broil, Half width broil, Hot Air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot air broiling, Hot Air-Eco, Roasting function, Top heat, Top heating, 1/3 bottom heat., warming

Cooking method secondary cavity

Baking stone function, Bottom heating, Bottom heating, 1/3 top heat., Defrosting, Dough proving setting, Hot air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot Air-Eco, Hot air grill, Large-area grill, Roaster function, Small area grill, Top/bottom heating, Top heating, Top heating, 1/3 bottom heat., Warming

Integrated Cleaning system

Self Clean

Number of interior lights

2

Timer

Yes

Included accessories

1 x enamel baking tray, suit. pyrolytic clean, 1 x rotary spit, 1 x grill shelf, 1 x grill tub with grid, 1 x pluggable meat probe

Bake Element Wattages primary cavity (W)

1700

Broil Element Wattages primary cavity (W)

3900

Convection Element Wattages primary cavity (W)

1900

Microwave Wattages (W)

Consumption and connection features

UPC code

825225957379

Product color

Stainless steel

Alternative colors available

Energy source

Electric

Watts (W)

9200

Current (A)

40

Volts (V)

208/220-240

Frequency (Hz)

60

Approval certificates

CSA, ETL, UL

Power Cord Length

70 7/8"

Plug type

fixed connection

Required cutout size (HxWxD) (in)

56 1/8 " x 28 1/2 " x 21 11/16 "

Overall appliance dimensions (HxWxD) (in)

56 1/4 " x 29 5/8 " x 21 9/16 "

Product packaging dimensions (HxWxD) (in)

69.48 x 33.07 x 29.72

Net weight (lbs)

330

Gross weight (lbs)

353

2019-11-01

Page 1

Rating

Total rating 9.2 kW.

Total Amps: 40 A.

208 / 220 - 240 V / 60 Hz.

Connection cable 70 7/8" without plug.

BX480612
400 series double oven
Stainless steel-backed full glass door
Width 30" (76 cm)
right-hinged
Controls centered
2019-11-01
Page 2

