



#### Color Variants

**BX481612**  
Stainless steel-backed full glass door  
Width 30" (76 cm)

#### Included accessories

1 x enamel baking tray, suit. pyrolytic clean.  
1 x rotary spit.  
1 x grill shelf.  
1 x grill tub with grid.  
1 x pluggable meat probe.

#### Optional accessories

**BA018165**  
Pull-out system  
**BA028115**  
Baking tray, enameled  
**BA038165**  
Wire rack, chromium-plated  
**BA058115**  
Heating element for baking stone and cast-iron roaster  
**BA058133**  
Baking stone  
**BS020002**  
Pizza peel, additional set of 2  
**GN340230**  
Non-stick aluminum cast-iron roaster

#### Product Variants

**BX480612**  
400 series double oven  
Stainless steel-backed full glass door  
Width 30" (76 cm)  
right-hinged  
Controls centered

**BX481612**  
400 series double oven  
Stainless steel-backed full glass door  
Width 30" (76 cm)  
left-hinged  
Controls centered

Pyrolytic self-cleaning system  
Universal heating system with 17 heating methods, with core temperature probe, rotisserie spit and baking stone operation  
Core temperature probe with estimation of cooking time  
TFT touch display  
Electronic temperature control from 85°F - 550°F  
2x 4.5 cu.ft. (110 litres) net volume.

#### Cooking modes

Convection.  
Economy convection..  
Top + bottom heat.  
Top + 1/3 bottom heat.  
Top heat.  
1/3 top + bottom heat.  
Bottom heat.  
Convection + bottom heat.  
Convection + 1/3 bottom heat.  
Convection broiling..  
Broiling.  
Compact grill.  
Baking stone operation.  
Roaster function.  
Dough proofing.  
Defrosting.  
Keeping warm.

#### Operation

Rotary knob and TFT touch display operation.  
Clear text display in 25 languages.  
Information key with use indicators.  
Side-opening door opens up to 180° angle.

#### Features

Three-point core temperature prove with automatic shut-off and estimation of cooking time.  
Rotisserie spit (lower oven).  
Baking stone outlet.  
Actual temperature display.  
Fast heating setting.  
Timer functions: cooking time, switch-off time, short-term timer, stopwatch.  
60 W halogen light on the top.  
10 W halogen light on the side.  
Enamelled side shelf supports with 5 tray levels, pyrolysis-safe.

#### Safety

Thermally insulated door with quadruple glazing.  
Child lock.  
Safety shut-off.  
Cooled housing with temperature protection.

#### Cleaning

Pyrolytic self-cleaning.  
Gaggenau Clean-Enamel.  
Heated air cleaning catalyst.

#### Planning notes

Door hinge not reversible.  
The front of the appliance extends 1 7/8" from the cabinet front.  
Consider the overhang when planning to open drawers next to the appliance.  
When planning a corner solution, pay attention to the 90° door opening angle.  
To achieve the 21 5/8" installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing.  
Plan a power outlet outside of the cut-out niche.

#### Product Features

##### Cooking mode

Baking stone function, Bottom heat, Bottom heating, 1/3 top heat., Conventional heat, Defrost, Dough proving setting, Full width broil, Half width broil, Hot Air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot air broiling, Hot Air-Eco, Roasting function, Top heat, Top heating, 1/3 bottom heat., warming

##### Cooking method secondary cavity

Baking stone function, Bottom heating, Bottom heating, 1/3 top heat., Defrosting, Dough proving setting, Hot air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot Air-Eco, Hot air grill, Large-area grill, Roaster function, Small area grill, Top/bottom heating, Top heating, Top heating, 1/3 bottom heat., Warming

##### Integrated Cleaning system

Self Clean

##### Number of interior lights

2

##### Timer

Yes

##### Included accessories

1 x enamel baking tray, suit. pyrolytic clean, 1 x rotary spit, 1 x grill shelf, 1 x grill tub with grid, 1 x pluggable meat probe

##### Bake Element Wattages primary cavity (W)

1700

##### Broil Element Wattages primary cavity (W)

3900

##### Convection Element Wattages primary cavity (W)

3900

##### Microwave Wattages (W)

#### Consumption and connection features

##### UPC code

825225957386

##### Product color

Stainless steel

##### Alternative colors available

##### Energy source

Electric

##### Watts (W)

9200

##### Current (A)

40

##### Volts (V)

208/220-240

##### Frequency (Hz)

60

##### Approval certificates

CSA, ETL, UL

##### Power Cord Length

70 7/8"

##### Plug type

fixed connection

##### Required cutout size (HxWxD) (in)

56 1/8 " x 28 1/2 " x 21 11/16 "

##### Overall appliance dimensions (HxWxD) (in)

56 1/4 " x 29 5/8 " x 21 9/16 "

##### Product packaging dimensions (HxWxD) (in)

69.09 x 33.46 x 29.72

##### Net weight (lbs)

357

##### Gross weight (lbs)

380

##### 2019-11-01

Page 1

## Rating

Total rating 9.2 kW.

Total Amps: 40 A.

208 / 220 - 240 V / 60 Hz.

Connection cable 70 7/8" without plug.

BX481612  
400 series double oven  
Stainless steel-backed full glass door  
Width 30" (76 cm)  
left-hinged  
Controls centered  
2019-11-01  
Page 2

