

Viking Undercounter/Freestanding Beverage Centers

Features

- Electronic controls with digital temperature readout
- Temperature can be adjusted from 36 to 48 degrees F (2.2-8.9 degrees C); factory set at 42 degrees F (5.6 degrees C)
- Can be displayed in either Fahrenheit or Celsius
- 5.3 cubic feet of storage on 24"W. models; 3.0 cubic feet of storage on 15"W. models
- One full extension adjustable wire shelf
- 75-lb. capacity
- 24"W. model accommodates 54 12-oz. cans
- 15"W. model accommodates 21 12-oz. cans
- Removable and adjustable
- Two full extension adjustable wine shelves
- 24"W. model accommodates 16 bottles
- 15"W. model accommodates 8 bottles
- Shelves can be removed and adjusted to store large bottles
- Dual pane and argon filled Low 'E' energy efficient glass doors
- LED display lighting

Construction and Design

- Forced air cooling system
- Powerful 700 BTU compressor
- Stainless steel interior
- Stainless steel exterior cabinet
- Tru-Flush™ design allows beverage center to fit flush into 24" deep installation cutout
- Undercounter or freestanding installation
- Self-closing door
- Super quiet 32-39 db sound rating
- Black kickplate
- Adjustable leveling legs

Models

- VBCI1240G – 24"W. Professional Beverage Center w/glass door (R/L)
- FBCI1240G – 24"W. Custom Panel Beverage Center w/glass door (R/L)
- VBCI1150G – 15"W. Professional Beverage Center w/glass door (R/L)
- FBCI1150G – 15"W. Custom Panel Beverage Center w/glass door (R/L)

Finish and Design Options

- VBCI models available in Stainless Steel (SS only) only
- FBCI models accept custom panels

Optional Accessories

- Professional handle kit for custom front models – PHK30SS



VBCI1240G

Warranty Highlights

- Three-year full – covers complete unit
 - Six-year full – sealed system
 - Lifetime limited – stainless steel exterior
 - 12-year limited – sealed system
 - Ninety-day limited – cosmetic parts such as glass, painted items, and decorative items
- * Warranty valid on Viking products shipped within the United States and Canada



Basic Specifications

Description	15"W. UNDERCOUNTER/FREESTANDING BEVERAGE CENTER	24"W. UNDERCOUNTER/FREESTANDING BEVERAGE CENTER
	VBCI/FBCI1150	VBCI/FBCI1240
Overall Width	14 7/8" (37.8 cm)	23 7/8" (60.6 cm)
Overall Height	34 1/4" (87.0 cm)	34 1/4" (87.0 cm)
Overall Depth from Rear	Without door panel: 23 5/16" (59.2 cm) To front of door panel: 24 1/16" (61.1 cm) To front of handle: 26 9/16" (67.5 cm)	
Cutout Width	15" (38.1 cm)	24" (61.0 cm)
Cutout Height	34 1/2"-35 1/2" (87.6-90.2 cm)	
Cutout Depth	24" (61.0 cm)	
Electrical Requirements	115V/60 Hz; 15 amp dedicated circuit; 5' power cord attached to product	
Maximum Amp Usage	3.0 amps	
Maximum Storage Capacity	5.3 cu. ft./16 wine bottles	3.0 cu. ft./8 wine bottles
Approximate Shipping Weight	175 lbs. (79 kg)	215 lbs. (98 kg)

Please do not prepare installation from brochure data only. See installation instructions for important clearance/installation information.



Viking Range Corporation
111 Front Street
Greenwood, Mississippi 38930 USA

(662) 455-1200

For product information, call 1-888-VIKING1 (845-4641),
or visit the Viking Web site at vikingrange.com



All models with standard equipment are design-certified for residential installation.

© 2011, Viking Range Corporation.

To receive the most current specification sheets, visit Dimension Express at www.dexpress.com or call from your fax machine at (925)284-3558. Enter code #8051 for Viking Products. This will send you information on how to use the system and the corresponding model code numbers. Dimension Express customer support can be reached by email at: support@dexpress.com.