

# ACR161WNSF456LHD



22.88" x 18.75" x 18.38" (H x W x D)

Compact healthcare all-refrigerator certified to NSF/ANSI 456 with self-closing solid door, front lock, digital controls, and NIST-calibrated temperature readout

**Highlights:**

- Certified to NSF/ANSI 456 Vaccine Storage Standard
- Specially designed to meet current CDC/VFC vaccine refrigeration guidelines for convenient storage in pharmacies, medical offices, and other healthcare facilities
- Designed and constructed for reliable cold storage in healthcare facilities

**Product Features:**

|                                                    |                                                                                                                                                                                                                                            |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EQTemp Healthcare Refrigerator                     | Refrigerator All-refrigerator designed to operate between 2 and 8°C for a variety of storage application in medical offices and other healthcare facilities                                                                                |
| Certified to NSF/ANSI 456 Vaccine Storage Standard | Tested to comply with the latest standards                                                                                                                                                                                                 |
| Certificate of calibration included                | The temperature monitoring device (TMD) is calibrated to NIST standards in our ISO/IEC 17025:2017 certified calibration laboratory and ships with a 2-year certificate of calibration for your records                                     |
| Temperature Range: 2° to 8°C                       | Preset to 5°C as recommended for many storage applications                                                                                                                                                                                 |
| Compact size                                       | Full 1.58 cu.ft. capacity inside conveniently slim footprint                                                                                                                                                                               |
| External temperature readout                       | Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button                                                                                      |
| High/low temperature alarm                         | Audible alarm sounds if the interior temperature rises or falls out of set range                                                                                                                                                           |
| Buffered temperature probe                         | Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines |

## ACR161WNSF456LHD Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Height of Cabinet          | 22.88" (58 cm)     |
| Width                      | 18.75" (48 cm)     |
| Width with Door Open       | 19.25" (49 cm)     |
| Depth                      | 18.38" (47 cm)     |
| Depth with door at 90°     | 35.63" (91 cm)     |
| Capacity                   | 1.58 cu.ft. (45 L) |
| Defrost Type               | Automatic          |
| Door                       | White              |
| Cabinet                    | White              |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Sanitation                 | ETL-S to NSF 456   |
| Amps                       | 0.6                |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 38.0 lbs. (17 kg)  |
| Shipping Weight            | 82.0 lbs. (37 kg)  |
| Parts & Labor Warranty     | 1 Year             |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101107660       |
| Refrigerator Features      |                    |
| Door Swing                 | LHD                |
| Reversible                 | Factory Reversible |
| Shelf Type                 | Wire               |
| Shelf Qty                  | 1                  |
| Thermostat Type            | Digital            |
| Fan Type                   | Interior           |
| Refrigerant Type           | R600a              |
| Refrigerant Amount         | 0.85oz.            |
| High Side PSI              | 1.45               |
| Low Side PSI               | 0.85               |
| Level Legs Qty             | 2                  |
| Interior Light             | Yes                |
| Temperature Range          | 2° to 8°C          |
| Sound Level                | 36.8 dB            |
| Dimensions                 |                    |
| Interior Height            | 16.63" (42 cm)     |
| Interior Width             | 15.63" (40 cm)     |

|                        |                |
|------------------------|----------------|
| Interior Depth         | 12.13" (31 cm) |
| Compressor Step Height | 7.75" (20 cm)  |
| Compressor Step Width  | 15.63" (40 cm) |
| Compressor Step Depth  | 5.25" (13 cm)  |

