

ARG3PV



34" x 18.5" x 19" (H x W x D)

Performance series Pharma-Vac 3 cu.ft. counter height glass door commercial all-refrigerator for the display and refrigeration of vaccines

Highlights:

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Additional sensor reads interior air temperature for superior temperature control

Product Features:

| | |
|---|--|
| Purpose-built design | Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines |
| +/-1°C Variation | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |
| Commercial design | Meets UL-471 commercial standards |
| Adjustable temperature | Intuitive controls let you adjust the interior temperature between +2 to +8°C |
| Temperature alarm | Visual and audible alarms alert if the interior temperature rises or falls out of set range |
| Remote alarm contacts | Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit) |
| Automatic defrost with adjustable cycle defrost | Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup |
| Access port | Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment |
| Open door alarm | Alarm will sound if the door is left ajar for over 4 minutes (adjustable from 1-99 minutes) |

ARG3PV Specifications:

| Overview | |
|----------------------------|-------------------|
| Height of Cabinet | 34.0" (86 cm) |
| Width | 18.5" (47 cm) |
| Width with Door Open | 19.0" (48 cm) |
| Depth | 19.0" (48 cm) |
| Depth with Handle | 20.75" (53 cm) |
| Depth with door at 90° | 36.0" (91 cm) |
| Capacity | 3.0 cu.ft. (85 L) |
| Defrost Type | Automatic |
| Door | Glass |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 0.6 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 86.2 lbs. (39 kg) |
| Shipping Weight | 93.2 lbs. (42 kg) |
| Estimated Time to Ship | 1 to 2 days |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| Refrigerator Features | |
| Door Swing | RHD |
| Reversible | Yes |
| Shelf Type | Wire |
| Shelf Qty | 4 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Refrigerant Type | R600a |
| Refrigerant Amount | 1.06oz. |
| Interior Light | Yes |
| Temperature Range | 2 to 8°C |
| Dimensions | |
| Interior Height | 28.38" (72 cm) |
| Interior Width | 15.25" (39 cm) |
| Interior Depth | 11.75" (30 cm) |
| Compressor Step Height | 8.0" (20 cm) |
| Compressor Step Width | 15.25" (39 cm) |
| Compressor Step Depth | 3.75" (10 cm) |

