

# ARS2PV



22.25" x 18.5" x 23.25" (H x W x D)

Performance series Pharma-Vac 2 cu.ft. compact all-refrigerator for vaccine storage with antimicrobial silver-ion handle and hospital grade cord with 'green dot' plug

### Highlights:

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Powder-coated handle with naturally occurring silver ions to help reduce germ spread

### Product Features:

Pharma-Vac Refrigerator	1.94 cu.ft. all-refrigerator purpose-built for vaccine storage
Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup
Access port	Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment
Open door alarm	Alarm will sound if the door is left ajar for over 4 minutes (adjustable from 1-99 minutes)

## ARS2PV Specifications:

Overview	
Height of Cabinet	22.25" (57 cm)
Width	18.5" (47 cm)
Width with Door Open	18.88" (48 cm)
Depth	23.25" (59 cm)
Depth with Handle	24.75" (63 cm)
Depth with door at 90°	42.5" (108 cm)
Capacity	1.94 cu.ft. (55 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.6
Voltage/Frequency	115 V AC/60 Hz
Weight	80.0 lbs. (36 kg)
Shipping Weight	98.5 lbs. (45 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101106625
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Wire
Shelf Qty	2
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	0.84oz.
High Side PSI	280.0
Low Side PSI	90.0
Interior Light	Yes
Temperature Range	2 to 8°C
Sound Level	44.2 dB
Dimensions	
Interior Height	16.5" (42 cm)
Interior Width	15.25" (39 cm)
Interior Depth	15.75" (40 cm)

Compressor Step Height	8.25" (21 cm)
Compressor Step Width	15.25" (39 cm)
Compressor Step Depth	4.25" (11 cm)

