

BIM44GADA



32.38" x 14.5" x 23.5" (H x W x D)

ADA compliant NSF-listed auto defrost clear icemaker with internal pump for built-in or freestanding use under counters

Highlights:

32 3/8" height fits under lower ADA compliant counters

Automatic defrost saves on user maintenance

Flexible design allows built-in or freestanding use

Product Features:

ADA compliant	32 3/8" height fits under lower ADA compliant counters
Commercially approved	NSF listed for use in commercial establishments
Built-in pump	Internal pump allows more flexibility in placing the unit
Automatic defrost	Simplify appliance care by letting your icemaker defrost itself
Reversible door	Keep your options flexible with a reversible door that is easy to switch when your arrangement changes; Unit ships LHD but can be reversed in our factory or by the user
Built-in capable	Make the best use of space by installing your icemaker under the counter
Stainless steel door	Professional styling with lasting durability
Professional towel bar handle	A curved handle in brushed stainless steel offers an easy grip
Fully finished black cabinet	Allows the icemaker to be used as a freestanding model







BIM44GADA Specifications:

Overview	
Height of Cabinet	32.38" (82 cm)
Width	14.5" (37 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.0" (64 cm)
Depth with door at 90°	36.75" (93 cm)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	NSF
Amps	4.8
Voltage/Frequency	115 V AC/60 Hz
Shipping Weight	117.0 lbs. (53 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Icemaker	
Icemaker Door Swing	LHD
	LHD Yes
Door Swing	
Door Swing Reversible	Yes
Door Swing Reversible Drain Required	Yes Yes
Door Swing Reversible Drain Required Daily Ice Production	Yes Yes 50.0 lbs. (23 kg)
Door Swing Reversible Drain Required Daily Ice Production Ice Storage Capacity	Yes Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg)
Door Swing Reversible Drain Required Daily Ice Production Ice Storage Capacity Ice Shape	Yes Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube
Door Swing Reversible Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube	Yes Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 3/4" x 3/4" x 1"
Door Swing Reversible Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Number of Ice Cube Sizes	Yes Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 3/4" x 3/4" x 1"
Door Swing Reversible Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Number of Ice Cube Sizes Fan Type	Yes Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 3/4" x 3/4" x 1" 1 Exterior
Door Swing Reversible Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Number of Ice Cube Sizes Fan Type Refrigerant Type	Yes Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 3/4" x 3/4" x 1" 1 Exterior R134a
Door Swing Reversible Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Number of Ice Cube Sizes Fan Type Refrigerant Type Refrigerant Amount	Yes Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 3/4" x 3/4" x 1" 1 Exterior R134a 3.88 oz.
Door Swing Reversible Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Number of Ice Cube Sizes Fan Type Refrigerant Type Refrigerant Amount High Side PSI	Yes Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 3/4" x 3/4" x 1" 1 Exterior R134a 3.88 oz. 350.0
Door Swing Reversible Drain Required Daily Ice Production Ice Storage Capacity Ice Shape Size of Cube Number of Ice Cube Sizes Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	Yes Yes 50.0 lbs. (23 kg) 25.0 lbs. (11 kg) Cube 3/4" x 3/4" x 1" 1 Exterior R134a 3.88 oz. 350.0 130.0



