

# **BIM68OSGDR**



#### 33.63" x 14.88" x 22.63" (H x W x D)

15" wide 62 lb. built-in undercounter commercially listed indoor/outdoor clear icemaker with gravity drain and complete stainless steel exterior finish

#### **Highlights:**

Weatherproof construction for use in the outdoors

Commercially approved to NSF-12 standards

Produces up to 62 lbs. of gourmet style clear ice cubes in a 24 hour cycle

### **Product Features:**

Commercially approved	ETL-S listed to NSF-12 commercial standards for use in foodservice settings
Weatherproof design	Durable construction for safe installation in outdoor kitchens
62 lb. production capacity	Can make up to 62 lbs. in a day cycle, producing 24 cubes in a 30 minute span
Built-in capable	Make the best use of space by installing your icemaker under the counter and flush with other cabinets
Stainless steel wrapped exterior	Door and cabinet are fully wrapped in 304 grade stainless steel for lasting elegance
Professional handle	Horizontally mounted towel bar style handle in stainless steel
Clear ice cube production	Gourmet style rounded dice-style ice cubes
Frost-free operation	No-frost operation for minimum user maintenance
Gravity drain setup	Requires connection to gravity drain

 $\checkmark$ 





## **BIM68OSGDR Specifications:**

Level Legs

Canadian Electrical SafetyETLSanitationETLAmps4Voltage/Frequency115 V AC/60 HWeight105.0 lbs. (48 k)	m) m) m) m) m) L) ee eel eel FL -C -S I.0 Hz
Width14.88" (38 crDepth22.63" (57 crDepth with Handle24.5" (62 crDepth with door at 90°37.25" (95 crCapacity0.98 cu.ft. (28Defrost TypeFrost-FrDoorStainless SterCabinetStainless SterUS Electrical SafetyETSanitationETLAmps4Voltage/Frequency115 V AC/60 FWeight105.0 lbs. (48 kr	m) m) m) L) ee ee ee FL -C -S I.0 Hz
Depth22.63" (57 cmDepth with Handle24.5" (62 cmDepth with door at 90°37.25" (95 cmOor0.98 cu.ft. (28Defrost TypeFrost-FreeDoorStainless SteeCabinetStainless SteeUS Electrical SafetyETLSanitationETLAmps4Voltage/Frequency115 V AC/60 FWeight105.0 lbs. (48 km	m) m) L) ee eel eel TL -C -S I.0 Hz
Depth with Handle24.5" (62 crDepth with door at 90°37.25" (95 crCapacity0.98 cu.ft. (28Defrost TypeFrost-FreDoorStainless SteCabinetStainless SteUS Electrical SafetyECanadian Electrical SafetyETLSanitationETLAmps4Voltage/Frequency115 V AC/60 FWeight105.0 lbs. (48 kr	m) m) L) ee ee eel eel TL -C -S I.0 Hz
Depth with door at 90°37.25" (95 cm 90°Capacity0.98 cu.ft. (28Defrost TypeFrost-From Frost-FromDoorStainless SteeCabinetStainless SteeUS Electrical SafetyETL SafetySanitationETL AmpsAmps4Voltage/Frequency115 V AC/60 F 105.0 lbs. (48 km)	m) L) ee ee eel FL -C -S I.0 Hz
90°Capacity0.98 cu.ft. (28)Defrost TypeFrost-FreDoorStainless SteCabinetStainless SteUS Electrical SafetyECanadian ElectricalETLSafetySanitationSanitationETLAmps4Voltage/Frequency115 V AC/60 FWeight105.0 lbs. (48 k	L) ee eel eel TL -C -S i.0 Hz
Defrost TypeFrost-FroDoorStainless SteCabinetStainless SteUS Electrical SafetyETCanadian ElectricalETLSafetySanitationSanitationETLAmps4Voltage/Frequency115 V AC/60 FWeight105.0 lbs. (48 k	ee eel eel TL -C -S I.0 Hz
DoorStainless SteCabinetStainless SteUS Electrical SafetyETCanadian Electrical SafetyETLSanitationETLAmps4Voltage/Frequency115 V AC/60 FWeight105.0 lbs. (48 k	el TL -C -S I.0 Hz
CabinetStainless SteUS Electrical SafetyECanadian ElectricalETLSafetySanitationSanitationETLAmps4Voltage/Frequency115 V AC/60 FWeight105.0 lbs. (48 k	eel TL -C -S I.0 Hz
US Electrical Safety E Canadian Electrical ETL Safety Sanitation ETL Amps 4 Voltage/Frequency 115 V AC/60 H Weight 105.0 lbs. (48 k	TL -C -S I.0 Hz
Canadian ElectricalETLSafetyETLSanitationETLAmps4Voltage/Frequency115 V AC/60 HWeight105.0 lbs. (48 k)	-C -S I.0 Hz
SafetySanitationAmps4Voltage/Frequency115 V AC/60 HWeight105.0 lbs. (48 k	-S I.0 Hz
Amps4Voltage/Frequency115 V AC/60 HWeight105.0 lbs. (48 k	I.O Hz
Voltage/Frequency115 V AC/60 HWeight105.0 lbs. (48 k	Ηz
Weight 105.0 lbs. (48 k	
<b>C</b>	
Chipping Maight 120.0 lbs (E4.14	g)
Shipping Weight 120.0 lbs. (54 k	(g)
Parts & Labor 1 Ye Warranty	ar
Compressor 5 Yea Warranty	irs
Icemaker	
Door Swing RF	ID
Reversible Y	és
Daily Ice Production 62.0 lbs. (28 k	g)
Ice Storage Capacity 26.0 lbs. (12 k	g)
Ice Shape Di	се
Size of Cube 1 1/4" H x 1 1/8" W x 1/8"	
Number of Ice Cube Sizes	1
Fan Type Exteri	ior
Refrigerant Type R134	4a
Refrigerant Amount 7.4 c	)Z.
High Side PSI 210	).0
Low Side PSI 105	5.0
Interior Width 12.75" (32 cr	m)
Interior Depth 9.25" (23 cr	



