

CL67ROSB



34" x 23.38" x 23.5" (H x W x D)

Outdoor all-refrigerator for built-in or freestanding use, with stainless steel exterior, black interior, front lock, and digital controls

Highlights:

304 grade stainless steel wrapped exterior offers lasting durability in outdoor kitchens

Flexible design allows built-in or freestanding use in 24" wide spaces

Factory installed lock provides security you can count on

Product Features:

Built-in capable	Front-breathing design lets you make the best use of space by installing your appliance under the counter	
Stainless steel exterior	Door and cabinet feature a 304 grade stainless steel finish designed to hold up to the elements	
Factory installed lock	Keyed lock for a secure interior, with two keys included	
Professional handle	Horizontally mounted handle with a thin diameter in brushed stainless steel to match many popular styles of cabinetry	
Frost-free operation	No-frost operation for minimum user maintenance	
Digital thermostat	Electronic controls located inside the unit for precise temperature management	
Door storage	Two door racks offer convenient storage for condiments and tall bottles	
Adjustable glass shelves	Rearrange refrigerator space to accommodate all sizes or remove shelves for simple cleanup	
Recessed LED lighting	Efficient and attractive lighting illuminates stored items for a full display	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

 \checkmark





CL67ROSB Specifications:

Height of Cabinet Width Depth Depth with Handle Depth with door at 90° Capacity Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Energy Usage/Year	34.0" (86 cm) 23.38" (59 cm) 23.5" (60 cm) 25.0" (64 cm) 45.63" (116 cm) 4.6 cu.ft. (130 L) Frost-Free Stainless Steel Stainless Steel Stainless Steel ETL-C ETL-C ETL-S 250.0kWh/year 1.0		
Depth Depth with Handle Depth with door at 90° Capacity Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation	23.5" (60 cm) 25.0" (64 cm) 45.63" (116 cm) 4.6 cu.ft. (130 L) Frost-Free Stainless Steel Stainless Steel Stainless Steel ETL ETL-C ETL-S 250.0kWh/year 1.0		
Depth with Handle Depth with door at 90° Capacity Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation	25.0" (64 cm) 45.63" (116 cm) 4.6 cu.ft. (130 L) Frost-Free Stainless Steel Stainless Steel ETL ETL-C ETL-S 250.0kWh/year 1.0		
Depth with door at 90° Capacity Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation	45.63" (116 cm) 4.6 cu.ft. (130 L) Frost-Free Stainless Steel Stainless Steel ETL ETL-C ETL-S 250.0kWh/year 1.0		
Capacity Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation	4.6 cu.ft. (130 L) Frost-Free Stainless Steel Stainless Steel ETL ETL-C ETL-S 250.0kWh/year 1.0		
Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation	Frost-Free Stainless Steel Stainless Steel ETL ETL-C ETL-S 250.0kWh/year 1.0		
Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation	Stainless Steel Stainless Steel ETL-C ETL-S 250.0kWh/year 1.0		
Cabinet US Electrical Safety Canadian Electrical Safety Sanitation	Stainless Steel ETL ETL-C ETL-S 250.0kWh/year 1.0		
US Electrical Safety Canadian Electrical Safety Sanitation	ETL ETL-C ETL-S 250.0kWh/year 1.0		
Canadian Electrical Safety Sanitation	ETL-C ETL-S 250.0kWh/year 1.0		
Safety Sanitation	ETL-S 250.0kWh/year 1.0		
	250.0kWh/year 1.0		
Energy Usage/Vear	1.0		
Lifergy Usage/ lear			
Amps	115 V AC/60 Hz		
Voltage/Frequency			
Weight	95.0 lbs. (43 kg)		
Shipping Weight	105.0 lbs. (48 kg)		
Estimated Time to Ship	1 to 2 days		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
Refrigerator Features			
Door Swing	RHD		
Reversible	Yes		
Shelf Type	Glass		
Shelf Qty	3		
Full Door Shelf Qty	2		
Adjustable Shelves	Yes		
Thermostat Type	Digital		
Fan Type	Interior and Exterior		
Refrigerant Type	R600a		
Refrigerant Amount	1.38oz.		
High Side PSI	270.0		
Low Side PSI	105.0		
Level Legs Qty	4		
Interior Light	Yes		
Temperature Range	36 to 43ºF		
Dimensions			

Interior Height	25.75" (65 cm)
Interior Width	19.0" (48 cm)
Interior Depth	17.25" (44 cm)
Compressor Step Height	3.5" (9 cm)
Compressor Step Width	19.0" (48 cm)
Compressor Step Depth	4.75" (12 cm)



