accucold

FS24L7MED2



21.75" x 18.5" x 17.63" (H x W x D)

Compact medical/scientific all-freezer with digital thermostat, NIST calibrated thermometer/alarm, and front lock

Highlights:

Specially designed and featured to meet the CDC and VFC's guidelines for safe vaccine storage

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Assembled in the USA from domestic and imported components

Product Features:

Reliable temperature stability	Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions
Digital thermostat	Electronic controls for more precise temperature management, with temperature readout and controls externally located for added convenience
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
Commercial design	ETL-S listed to ANSI-NSF Standard 7 for facilities with commercial requirements
NIST calibrated temperature display	Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle to maintain temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines
Factory installed lock	Keyed lock for convenient security, with two keys included
Manual defrost	Static cooling system for reduced temperature fluctuations
Hospital grade cord and plug	Secure three-pronged cord for added unit safety

ACCUCOLD DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799



accucold

FS24L7MED2 Specifications:

Overview	
Height of Cabinet	21.75" (55 cm)
Width	18.5" (47 cm)
Depth	17.63" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.4 cu.ft. (40 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	40.0 lbs. (18 kg)
Shipping Weight	65.0 lbs. (29 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	14.38" (37 cm)
Interior Width	$40 \Gamma^{\parallel} (04 \text{ams})$
	13.5" (34 cm)
Interior Depth	13.25" (34 cm) 13.25" (34 cm)
Interior Depth Shelf Type	,
•	13.25" (34 cm)
Shelf Type	13.25" (34 cm) Wire
Shelf Type Shelf Qty	13.25" (34 cm) Wire 1
Shelf Type Shelf Qty Thermostat Type	13.25" (34 cm) Wire 1 Digital
Shelf Type Shelf Qty Thermostat Type Refrigerant Type	13.25" (34 cm) Wire 1 Digital R134a
Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount	13.25" (34 cm) Wire 1 Digital R134a 1.5 oz.
Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI	13.25" (34 cm) Wire 1 Digital R134a 1.5 oz. 280.0
Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	13.25" (34 cm) Wire 1 Digital R134a 1.5 oz. 280.0 110.0
Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs	13.25" (34 cm) Wire 1 Digital R134a 1.5 oz. 280.0 110.0 2
Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Compressor Step Height	13.25" (34 cm) Wire 1 Digital R134a 1.5 oz. 280.0 110.0 2 8.5" (22 cm)

