

SBC56GBINKCSSADA



32.25" x 23.63" x 23" (H x W x D)

Built-in undercounter ADA height commercially listed beer dispenser with glass door, lock, and stainless steel wrapped cabinet; no tapping equipment included

Highlights:

32 inch height fits under lower ADA compliant counters

Commercially listed to NSF-7 standards

Flexible design allows built-in or freestanding use in 24" spaces

Product Features:

ADA compliant height	Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings
Built-in capable	Front-breathing design allows fully recessed installation under counters
Tap kit not included	Install your own tapping equipment to create a customized beer cooler
Designed for 1/6 kegs	Interior can store up to two sixtel kegs
Double pane tempered glass door	Heat resistant design provides clear view to promote impulse buys
Stainless steel wrapped cabinet	Exterior features a wrapped stainless steel finish for lasting durability in busy commercial settings
Professional handle	Curved towel bar style handle in brushed stainless steel
Factory-installed lock	Keyed lock conveniently located towards the top of the door for added security (2 keys included)



SBC56GBINKCSSADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.0" (58 cm)
Depth with Handle	25.5" (65 cm)
Depth with door at 90°	44.5" (113 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatic
Door	Glass
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.8
Voltage/Frequency	115 V AC/60 Hz
Weight	110.0 lbs. (50 kg)
Shipping Weight	110.0 lbs. (50 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101062860
Keegerator	
Door Swing	RHD
Reversible	Factory Reversible
Thermostat Type	Dial
Interior Light	Yes
Fan Type	Exterior
Refrigerant	R600a
Refrigerant Amount	0.67 oz.
High Side PSI	124.0
Low Side PSI	30.0
Inter Height	26.0" (66 cm)
Interior Width	21.0" (53 cm)
Interior Depth	18.0" (46 cm)
Compressor Step Height	7.0" (18 cm)
Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	34° to 43°F

