

# SBC58BLBIADAIFCMTWIN



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap combo nitro/cold brew coffee dispenser with panel-ready door and black cabinet

### Highlights:

32 inch height fits under lower ADA compliant counters

Commercial grade tap kit includes everything you need to serve both flat iced cold brew and creamy nitro brew drafts

Commercially listed to NSF-7 standards

### Product Features:

|                                      |   |
|--------------------------------------|---|
| Dispenses both flat and nitro coffee | Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro drafts  |
| ADA compliant height                 | Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters  |
| Commercially approved                | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings   |
| Built-in capable                     | Front-breathing design lets you make the best use of space by installing your appliance under the counter   |
| Complete tap kit                     | Commercial grade tap kit includes a dual tap draft tower with a standard and stout tap, Nitrogen tank, dual gauge regulator, and connections for ball lock Cornelius kegs   |
| Dual tap system                      | Twin style draft tower allows you to serve from two cornelius style kegs  |
| Panel-ready door                     | Customize the front by mounting an overlay panel over the door; seamless look can blend into other cabinetry with no exposed frame. Handle not included (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.) |
| Adjustable thermostat                | Interior dial thermostat ensures easy temperature management  |

Automatic defrost No frost operation for minimum user maintenance



## SBC58BLBIADAIFCMTWIN Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Height of Cabinet          | 32.0" (81 cm)      |
| Height to Hinge Cap        | 32.25" (82 cm)     |
| Width                      | 23.63" (60 cm)     |
| Depth                      | 22.75" (58 cm)     |
| Depth with door at 90°     | 45.0" (114 cm)     |
| Capacity                   | 5.5 cu.ft. (156 L) |
| Defrost Type               | Automatic          |
| Door                       | Panel-Ready        |
| Cabinet                    | Black              |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Sanitation                 | ETL-S              |
| Amps                       | 1.2                |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 110.0 lbs. (50 kg) |
| Shipping Weight            | 125.0 lbs. (57 kg) |
| Parts & Labor Warranty     | 1 Year             |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101069678       |
| Kegerator                  |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Tap Kit                    | Yes                |
| Number of Taps             | 2                  |
| Thermostat Type            | Dial               |
| Interior Light             | Yes                |
| Fan Type                   | Exterior           |
| Refrigerant                | R600a              |
| Refrigerant Amount         | 0.64 oz.           |
| High Side PSI              | 180.0              |
| Low Side PSI               | 80.0               |
| Inter Height               | 25.75" (65 cm)     |
| Interior Width             | 21.0" (53 cm)      |
| Interior Depth             | 17.75" (45 cm)     |
| Compressor Step Height     | 6.5" (17 cm)       |
| Compressor Step Width      | 21.0" (53 cm)      |
| Compressor Step Depth      | 5.5" (14 cm)       |

### Temperature Range

