

SBC7BRSCF2



33.5" x 23.63" x 22.38" (H x W x D)

24" wide commercially approved cold brew coffee dispenser made in Europe with a twin tap kit to store and serve from two 1/6 kegs; includes adjustable legs and caster set for optional mobility

Highlights:

Made in Europe

Dual tap system lets you serve from two sixtel kegs

Designed for recessed installation or portable use with a caster set included

Product Features:

| | |
|---|--|
| 24" Wide Cold Brew Coffee Dispenser | Kegeator includes all of the equipment you need to serve cold brew coffee from two sixtel kegs |
| Made in Europe & the USA | Refrigeration unit is constructed in Europe and designed and modified in the USA |
| Versatile use | Approved for both residential and commercial settings |
| Commercially listed | ETL-S listed to ANSI-NSF Standard 7 for commercial use |
| Complete dual tap coffee kit | Commercial grade tap kit includes a dual tap stainless steel draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs |
| Dual tap system | Twin draft tower allows you to serve from two 1/6 (sixel) sized kegs |
| Slim counter height dimensions for recessed or freestanding use | Ideal 24" footprint for an easy fit |
| Height adjustable | Adjustable legs allow you to set the height anywhere between 33.5" and 34.5" to best fit under your counter |
| Leg shield included | Removable cover that lets you fill the gap that can appear between the refrigerator's kickplate and floor when raising the height |

SBC7BRSCF2 Specifications:

| Overview | |
|----------------------------|---------------------|
| Height of Cabinet | 33.5" (85 cm) |
| Width | 23.63" (60 cm) |
| Depth | 22.38" (57 cm) |
| Depth with Handle | 24.0" (61 cm) |
| Depth with door at 90° | 44.25" (112 cm) |
| Capacity | 5.3 cu.ft. (150 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Black |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Energy Usage/Year | 293.0kWh/year |
| Amps | 0.8 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 100.0 lbs. (45 kg) |
| Shipping Weight | 136.5 lbs. (62 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101106144 |
| Kegeerator | |
| Door Swing | RHD |
| Reversible | Yes |
| Height Adjustable | Yes |
| Tap Kit | Yes |
| Number of Taps | 2 |
| Adjustable Shelves | Yes |
| Shelf Type | Glass and Scalloped |
| Shelf Qty | 4 |
| Thermostat Type | Dial |
| Interior Light | Yes |
| Refrigerant | R600a |
| Refrigerant Amount | 0.64 oz. |
| Inter Height | 27.75" (70 cm) |
| Interior Width | 21.0" (53 cm) |
| Interior Depth | 18.0" (46 cm) |

| | |
|------------------------|---------------|
| Compressor Step Height | 5.5" (14 cm) |
| Compressor Step Width | 21.0" (53 cm) |
| Compressor Step Depth | 6.0" (15 cm) |
| Level Legs Qty | 4 |
| Wheel Qty | 4 |
| Temperature Range | 36 to 46°F |

