

SCFM183



32.5" x 65.25" x 29.25" (H x W x D)

Commercially listed 17.2 cu.ft. manual defrost chest freezer in white with stainless steel corner guards and lock

Highlights:

Commercially approved for use in foodservice establishments

17.2 cu.ft. interior for large capacity storage

Manual defrost operation and static cooling system

Product Features:

Large capacity	17.2 cu.ft. of interior storage	
Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for commercial use	
Lock included	Ships with a keyed lock and two keys for optional installation on the lid	
Manual defrost operation	Static cooling system with a front drain for easier defrosting as needed	
Counterbalanced hinges	The lid will remain open once lifted for easier loading	
Thick insulation	3 1/2" thick walls ensure proper insulation for reliable storage	
Stainless steel front corner protectors	Factory-installed external "bumpers" to help protect the corners in busy high traffic environments	
Hammered aluminum interior	Solid construction for durable storage in busy settings	
Easy-grip handle	External handle for easy opening (ships unsassembled)	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799





SCFM183 Specifications:

Overview		
Height of Cabinet	32.5" (83 cm)	
Width	65.25" (166 cm)	
Depth	29.25" (74 cm)	
Depth with Handle	31.0" (79 cm)	
Capacity	17.2 cu.ft. (487 L)	
Defrost Type	Manual	
Door	White	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Amps	3.6	
Voltage/Frequency	115 V AC/60 Hz	
Weight	200.0 lbs. (91 kg)	
Shipping Weight	210.0 lbs. (95 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101080819	
Freezer		
Door Swing	Lift-Up	
Interior Height	25.0" (64 cm)	
Interior Width	59.0" (150 cm)	
Interior Depth	21.5" (55 cm)	
Thermostat Type	Dial	
Refrigerant Type	R290a	
Refrigerant Amount	2.89 oz.	
High Side PSI	400.0	
Low Side PSI	200.0	
Wheels	6	
Compressor Step Height	10.25" (26 cm)	
Compressor Step Width	11.75" (30 cm)	
Compressor Step Depth	21.5" (55 cm)	
Temperature Range	-10 to -26°C	



