

## **SCFM203**



32.63" x 76" x 28.25" (H x W x D)

Commercially listed 19.8 cu.ft. manual defrost chest freezer in white with stainless steel corner guards and lock

## **Highlights:**

Commercially approved for use in foodservice establishments

19.8 cu.ft. interior for large capacity storage

Manual defrost operation and static cooling system

## **Product Features:**

Large capacity	19.8 cu.ft. of interior storage
Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for commercial use
Factory installed lock	Keyed lock for a secure interior (2 keys included)
Manual defrost operation	Static cooling system with a rear-mounted drain for easier defrosting as needed
Counterbalanced hinges	The lid will remain open once lifted for safer loading
Thick insulation	3 1/2" thick walls ensure proper insulation for reliable storage
Stainless steel front corner protectors	External "bumpers" included for easy installation to help protect the corners in high traffic environments
Hammered aluminum interior	Solid construction for durable storage in busy settings
Easy-grip handle	External handle for easy opening







## **SCFM203 Specifications:**

Overview		
Height of Cabinet	32.63" (83 cm)	
Width	76.0" (193 cm)	
Depth	28.25" (72 cm)	
Depth with Handle	30.0" (76 cm)	
Capacity	19.8 cu.ft. (561 L)	
Defrost Type	Manual	
Door	White	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Amps	3.6	
Voltage/Frequency	115 V AC/60 Hz	
Weight	205.0 lbs. (93 kg)	
Shipping Weight	210.0 lbs. (95 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101080802	
Freezer		
Door Swing	Lift-Up	
Interior Height	24.25" (62 cm)	
Interior Width	70.25" (178 cm)	
Interior Depth	20.75" (53 cm)	
Thermostat Type	Dial	
Refrigerant Type	R290a	
Refrigerant Amount	3.03 oz.	
High Side PSI	400.0	
Low Side PSI	200.0	
Wheels	6	
Compressor Step Height	10.25" (26 cm)	
Compressor Step Width	11.75" (30 cm)	
Compressor Step Depth	20.75" (53 cm)	
Temperature Range	-10 to -26°C	

