

SCRR492



83.75" x 55.25" x 31" (H x W x D)

49 cu.ft. commercial reach-in refrigerator in complete stainless steel with glass doors

Highlights:

Commercially listed to NSF standards

Stainless steel interior and exterior cabinet for true durability in high traffic commercial settings

Optimized forced air cooling for excellent temperature stability and uniformity with rapid recovery after door openings and product loading

Product Features:

| Complete stainless steel construction | Interior and exterior are entirely constructed from stainless steel for lasting durability and easy cleanup |
|---|---|
| Forced air cooling | Top-mounted commercial fan ensures rapid temperature recovery |
| Automatic defrost with adjustable cycle defrost | Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup |
| Self-closing doors | Closes to save energy but will remain open when the door is opened at a 90° angle for easier loading |
| Open door alarm | Alarm will beep 3 times if the door is left open for 30 seconds, 5 times at 60 seconds, and will sound continuously if the door is open for more than 5 minutes |
| Temperature alarm | Visual and audible alarms alert if the interior temperature rises or falls out of set range |
| 6 inch casters | Ships with a set of casters (2 locking) for optional user installation |
| Microprocessor control panel | Digital controls with a large LED readout in Celsius or Fahrenheit for intuitive temperature management |
| Min/max display | Control panel provides a readout of the low and high temperatures in 15 minute increments |



SCRR492 Specifications:

| Overview | |
|---|---|
| Height of Cabinet | 83.75" (213 cm) |
| Width | 55.25" (140 cm) |
| Depth | 31.0" (79 cm) |
| Depth with Handle | 31.0" (79 cm) |
| Depth with door at 90° | 56.5" (144 cm) |
| Capacity | 49.0 cu.ft. (1388 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Stainless Steel |
| US Electrical Safety | UL |
| Canadian Electrical Safety | ULC |
| Sanitation | ETL-S |
| Amps | 7.5 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 441.0 lbs. (200 kg) |
| Shipping Weight | 460.0 lbs. (209 kg) |
| Estimated Time to Ship | 1 to 2 Days |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| Refrigerator Features | |
| Dana Custan | |
| Door Swing | French |
| Shelf Type | French Wire |
| | |
| Shelf Type | Wire |
| Shelf Type Shelf Qty | Wire 8 |
| Shelf Type Shelf Qty Adjustable Shelves | Wire 8 Yes |
| Shelf Type Shelf Qty Adjustable Shelves Thermostat Type | Wire 8 Yes Digital |
| Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type | Wire 8 Yes Digital Interior |
| Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type | Wire 8 Yes Digital Interior R290a |
| Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount | Wire 8 Yes Digital Interior R290a 3.2oz. |
| Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI | Wire 8 Yes Digital Interior R290a 3.2oz. 290.0 |
| Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI | Wire 8 Yes Digital Interior R290a 3.2oz. 290.0 155.0 |
| Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Wheel Qty | Wire 8 Yes Digital Interior R290a 3.2oz. 290.0 155.0 |
| Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Wheel Qty Interior Light | Wire 8 Yes Digital Interior R290a 3.2oz. 290.0 155.0 4 Yes |
| Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Wheel Qty Interior Light Temperature Range | Wire 8 Yes Digital Interior R290a 3.2oz. 290.0 155.0 4 Yes |
| Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Wheel Qty Interior Light Temperature Range Dimensions | Wire 8 Yes Digital Interior R290a 3.2oz. 290.0 155.0 4 Yes 33 to 41°F |

