## accuc@ld

# **VLT204**



32.63" x 76" x 28.25" (H x W x D)

-35°C laboratory 19.8 cu.ft. chest freezer with stainless steel corner guards, NIST calibrated thermometer with alarm, and lock

### **Highlights:**

Designed to operate at -35°C for select laboratory, pharmacy, industrial, and other institutional storage needs

Includes an external NIST calibrated readout of the current and high/low temperature with an audible alarm

Manual defrost operation and static cooling system

#### **Product Features:**

| Low temperature chest freezer       | Operates at -35°C for use in laboratories, research facilities, and other settings with lower temperature cold storage needs   |
|-------------------------------------|--|
| NIST calibrated temperature display | Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button  |
| High/low temperature alarm          | Audible alarm sounds if the interior temperature rises or falls out of set range   |
| Certificate of calibration          | 2-year certificate included for your records   |
| Buffered temperature probe          | Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines |
| Factory-installed lock              | Added security with a locking lid (2 keys included)  |
| Manual defrost operation            | Static cooling system with a front drain for easier defrosting as needed   |
| Digital controls                    | Externally located digital thermostat allows you to adjust the temperature as needed without opening the lid   |
| Counterbalanced hinges              | The lid will remain open once lifted for easier loading  |

## accuc@ld

### **VLT204 Specifications:**

| Overview                      |                     |
|-------------------------------|---------------------|
| Height of Cabinet             | 32.63" (83 cm)      |
| Width                         | 76.0" (193 cm)      |
| Depth                         | 28.25" (72 cm)      |
| Depth with Handle             | 31.0" (79 cm)       |
| Capacity                      | 19.8 cu.ft. (561 L) |
| Defrost Type                  | Manual              |
| Door                          | White               |
| Cabinet                       | White               |
| US Electrical Safety          | ETL                 |
| Canadian Electrical<br>Safety | ETL-C               |
| Sanitation                    | ETL-S               |
| Amps                          | 3.6                 |
| Voltage/Frequency             | 115 V AC/60 Hz      |
| Weight                        | 205.0 lbs. (93 kg)  |
| Shipping Weight               | 210.0 lbs. (95 kg)  |
| Parts & Labor Warranty        | 1 Year              |
| Compressor Warranty           | 5 Years             |
| UPC                           | 761101086446        |
| Freezer                       |                     |
| Door Swing                    | Lift-Up             |
| Interior Height               | 24.25" (62 cm)      |
| Interior Width                | 70.25" (178 cm)     |
| Interior Depth                | 20.75" (53 cm)      |
| Thermostat Type               | Digital             |
| Refrigerant Type              | R290a               |
| Refrigerant Amount            | 3.03 oz.            |
| High Side PSI                 | 400.0               |
| Low Side PSI                  | 200.0               |
| Wheels                        | 6                   |
| Compressor Step Height        | 10.25" (26 cm)      |
| Compressor Step Width         | 11.75" (30 cm)      |
| Compressor Step Depth         | 20.75" (53 cm)      |

