



#### Color Variants

CI282610  
Stainless steel frame  
Width 30"

#### Optional accessories

CA051300  
Teppan Yaki made of multi ply material  
GP900001  
Stainless steel frying sensor pan.  
GP900002  
Stainless steel frying sensor pan.  
GP900003  
Stainless steel frying sensor pan.

#### 200 series Flex induction cooktop

CI282610

Stainless steel frame

Width 30"

Stainless steel frame.  
Flex function for combining the rectangular cooking areas  
Free positioning of cookware inside combined cooking areas  
Cooking sensor function for temperature control in pots  
Frying sensor function for temperature control in pans  
Twist-Pad control - the maneuverable magnetic knob sets cooking zone and temperature.  
Easy control of all functions with bicoloured display

#### Cooking zones

2 flex induction cooking areas 7 1/2" x 9" (2,200 W, with booster 3,600 W), linked together 15" x 9" (3300 W, with Power boost 3600 W).  
1 induction cooking zone ø 11" (2600 W, with Power boost 3700 W).  
1 induction cooking zone ø 6" (1400 W, with Power boost 2200 W).

#### Operation

Twist-Pad control with removable magnetic knob.  
User friendly control with bicoloured display (white / orange).  
Electronic power control in 17 power levels.

#### Features

Cooking sensor function (in use with cooking sensor CA 060 600).  
Frying sensor function.  
Booster function for pots.  
Booster function for pans.  
Keep warm function.  
Cooking timer for up to 99 minutes.  
Short-time timer.  
Options menu  
Power management.

#### Safety

Main switch.  
Operation indication.  
Pan detection.  
Child lock.  
Safety shut-off.

#### Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended.  
The wok pan WP 400 001 cannot be used with this appliance.  
Immersion depth depending on installation situation, 2 5/8" for surface-mount or 2 3/4" for flush-mount.  
Intermediate shelf is recommended.  
Appliance must be fixed from underneath.  
Cooktop clamping range: 1 3/16" - 1 9/16".

#### Rating

Total rating 10.8 kW.  
Total Amps: 30 A.  
208 - 240 V / 60 Hz  
Connecting cable 60" without plug (hardwire required).

#### Product Features

Knob Material  
Sealed Burners  
No  
Burners with booster  
All  
Type of grate  
Total BTU load  
LP Gas Connection Rating (BTU)  
Power of heating element (kW in boost)  
3.6  
Dimension of 1st heating element (in)  
Power of 2nd heating element (kW in boost)  
3.6  
Dimension of 2nd heating element (in)  
Power of 3rd heating element (kW in boost)  
Dimension of 3rd heating element (in)  
Power of 4th heating element (kW in boost)  
Dimension of 4th heating element (in)  
Power of 5th heating element (kW in boost)  
3.7  
Dimension of 5th heating element (in)  
11"  
Power of 6th heating element (kW in boost)  
Dimension of 6th heating element (in)

#### Consumption and connection features

UPC code  
825225919834  
Variant color  
Black  
Energy source  
Electric  
Gas type  
Alternative gas type  
Watts (W)  
Current (A)  
30  
Volts (V)  
208-240  
Frequency (Hz)  
60  
Approval certificates  
CSA  
Power Cord Length  
37"  
Plug type  
no plug  
Required cutout size (HxWxD) (in)  
Minimum distance from counter front (in)  
2 1/2"  
Minimum distance from rear wall (in)  
2 3/8"  
Overall appliance dimensions (HxWxD) (in)  
1/8"+4 1/4" x 31 3/4" x 20 1/2"  
Product packaging dimensions (HxWxD) (in)  
6.77 x 26.77 x 36.41  
Net weight (lbs)  
45  
Gross weight (lbs)  
54  
Total number of cooktop burners  
4  
2017-04-06  
Page 1

