

COOKTOPS

30-INCH INDUCTION

CIT304KB / CIT304KM / CIT304KBB



MASTERPIECE

CIT304KB – Black Finish



MASTERPIECE

CIT304KM – Silver Mirrored Finish



MASTERPIECE

CIT304KBB – Frameless

Product available 3rd Quarter 2012. For our current collection of Induction Cooktops, refer to Volume 1 of the Kitchen Design and Planning Guide or visit thermador.com or your local dealer for details.

CIT304KB / CIT304KM / CIT304KBB

INNOVATION

- ★ - New, redesigned Silver Mirrored Finish – striking and bold design offers the perfect companion solution for stainless steel products (CIT304KM)

PERFORMANCE

- Speed Heating – Induction cooktops heat 50% faster than traditional gas cooktops
- Large and powerful 11" element with 3,600 W
- Our Induction PowerBoost® feature heats cookware faster than any other type of cooking technology.
- Auto Shut-Off Timer available for all elements enables user to set desired cooking times. Separate kitchen timer also available.
- Keep Warm function allows meals to remain ready to serve
- Pan Recognition – Element will not turn on if other small objects are placed on the cooking zone
- Anti-Overflow System – exclusive feature prevents spills by automatically shutting off and sounding alarm when liquids are detected on surface
- 2-step digital control panel indicates when elements are hot or very hot
- Child safety lock

DESIGN






- Touch control panel with blue light illumination offers 17 power settings
- Chiseled, angular design coordinates with the suite of Thermador Masterpiece™ Collection appliances
- Full stainless steel frame (CIT304KB)
- Trapezoid design control panel
- New – Now available in black with frameless design (CIT365KBB)

SPECIFICATIONS

| | |
|--|-------------------------|
| Total Number of Cooktop Elements | 4 |
| Product Width | 31" |
| Product Depth | 21 1/4" |
| Cutout Width | 28 3/4" – 28 7/8" |
| Cutout Height | 3 1/8" |
| Minimum Air Clearance | 1" |
| Total Cutout Height (Including Air Clearance) | 4 1/8" |
| Cutout Depth | 19 7/8" – 20" |
| Minimum Distance from Counter Front | 2 1/4" |
| Minimum Distance from Rear Wall | 2" |
| Left Front Element (Size / W / W with PowerBoost) | 9" / 2,200 W / 3,700 W |
| Right Front Element (Size / W / W with PowerBoost) | 6" / 1,400 W / 1,800 W |
| Left Rear Element (Size / W / W with PowerBoost) | 6" / 1,400 W / 1,800 W |
| Right Rear Element (Size / W / W with PowerBoost) | 11" / 2,400 W / 3,600 W |
| Electrical Supply | 240/208V AC, 60 Hz |
| Required Circuit Breaker | 40 Amp |
| Conduit | 39" Flexible 3-Wire |
| Shipping Weight (lbs.) | 49 |



ACCESSORIES

| | | | | | |
|---|------------------------------|---|------------------------------|---|---------------------------------|
|  | SENSORPOT9 9" Ceramic Pot |  | SENSORPOT6 6" Ceramic Pot |  | CHEFSPAN13 16" Round Skillet |
|  | SENSORPOT7 7" Ceramic Pot |  | SENSORPOTH 6" Ceramic Pot | | |