




Installation is simplified with the Custom Hood Liner insert. All-in-one design includes everything you need to achieve a fully integrated appéarance.







A.Installation height above the cooking surface 24–30"

B.The distance from bottom of range hood to top of range hood: 11"

HVI certified performance

Heat Sentry[™] detects excessive heat and adjusts speed to high automatically

Separate On/Off speed control gives you the convenience of automatically remembering favorite setting.

Standard stainless steel is not recommended for installations along saltwater coastal areas

CFM Reducer Kit for CP35 reduces max CFM to 250–300

Available only in the U.S.

Hood Sizes

Widths 28-7/16", 34-7/16", 40-7/16" on CP35; 46-7/16" on CP37 Depths 19-5/16" on CP35; 22-9/16" on CP37

Blower Included

Finish

Stocked	Brushed Standard Grade
	Stainless Steel (See Sidebar)
Special Order	Not Available

Features		
Light Type	Halogen, MR16; GU10-50W	
Number of Lamps	2	
Lighting Levels	2	
Lighting Lamps Included	Yes	
Control Type	Variable Speed, Rotary with Separate On/Off Control	
Control Features	Heat Sentry [™]	
Control Remote	Not Available	
Filter: Standard	Stainless Steel Baffle	
Filter: Options	Not Available	
Non-ducted Capability	No	
	Light Type Number of Lamps Lighting Levels Lighting Lamps Included Control Type Control Features Control Remote Filter: Standard Filter: Options	

Blower (Included) Choose from 600 CFM or 1200 CFM

DIOWCI (IIIC	idaca, choo.	SC ITOTTI OOO CI IVI C	71 1200 CI IVI
Internal Blowe	er Model	CP35	CP37
Vertical CFM	High/Low	600/190	1200/380
Vertical Sones	High/Low	12.0/2.0	13.5/2.0

Accessories

Non-ducted Recirculating Kit	Not Available
Decorative Trim	Not Available
Liners	Not Available
CFM Reducer Kit	ARP8, for CP35 only

Installation Doquiromonto

installation Requirements	
Amps @ 120V	CP35: 6 Amps, CP37: 9 Amps
Electrical	Direct Wire
Duct Size: Internal Blower	CP35: 8" Round, CP37: 10" Round
Duct Direction	Vertical

Included







BESTRANGEHOODS.COM

926 WEST STATE STREET HARTFORD, WISCONSIN 53027 800-558-1711, IN CANADA 866-737-7770



The Custom Hood Liner easy install system comes with liner, blower, filtration, controls, lighting and damper.



Rotary controls for two-level lighting and variable blower speeds enable the user to choose operating