

CT66J

33.25" x 23.63" x 23.5" (H x W x D)

SUMMIT

Freestanding refrigerator-freezer with SUMMIT's "dual evaporator" cooling and cycle defrost

Highlights:

Ice cream stays frozen in zero degree freezer

Improved temperature performance with SUMMIT's dual evaporator cooling

the freezer with two evaporators

Over five cubic feet of storage

Perfectly sized to fit in tight 24 inch spaces



Slim undercounter dimensions	Our unique 24" wide models offer full capacity in a slim fit
Zero degree freezer	Keep ice cream frozen and freezer burn-free in a freezer that reaches and maintains zero degrees
Cycle defrost	Combines an automatic defrosting refrigerator with a manual defrosting freezer to save energy but protect food
Adjustable thermostat	Control your food's temperature with ease and accuracy
Interior light	Automatically illuminates when you open the door
Adjustable glass shelves	Rearrange your refrigerator space to accommodate all shapes and sizes or remove shelves for a simple clean-up
Fruit and vegetable crisper	Get the longest life and best taste out of produce by storing it in a convenient slide drawer
Door storage	Store large bottles right on the door for easy access
Reversible door	Keep your options flexible with a reversible door that's easy to switch when your arrangement changes
Dual evaporator	SUMMIT's unique and efficient design separately cools the refrigerator while maintaining zero degrees in

Specifications:

33.25" 23.63" 23.5" 5.1 cu.ft. 19.5" 20.5" 17.0" 19.0" 11.5"	LC.	2528	5'-0"LG. ELEC		193
23.5" 5.1 cu.ft. 19.5" 20.5" 17.0" 5.0" 19.0"	LC.	222 8	TOP VIEW		
5.1 cu.ft. 19.5" 20.5" 17.0" 5.0" 19.0"	LC.	88.	TOP VIEW	8	€ 4
19.5" 20.5" 17.0" 5.0" 19.0"	LC.	8823	TOP VIEW	8	€4
20.5" 17.0" 5.0" 19.0" 11.5"	L	228	TOP VIEW		<u>ო</u> 4
17.0" 5.0" 19.0" 11.5"	LC (2228	TOP VIEW		დ_4
5.0" 19.0" 11.5"	L.	222	TOP VIEW	li li	ω 4
19.0" 11.5"	•	72	TOP VIEW		o
11.5"			TOT VIEVV		_
				7	
20.5"				-	
		1-6			,
		,			-4
		ð			45 1
		•			
	Υ,	12			
				1 111	
1					
				1 111	
				1 11 1	
			5		
			238	-	
3					
					+ 1
33.5"					•
45.13"					7
true		I ATT ATT	III. OTHER		100000
Dial					
R134a				- 4	
285.0				\longrightarrow	
2	r Appliands	e Autho	ritym	1	
70.0					
2.6				7	
1 Year		FRON	AT VIEW	4	33,1
5 Years					
5 1 1 L L 1 4 Y F 1 3 C T 1 2 7 2	3.0" 02.0 lbs. 3 JL JLC 15 V AC/60 Hz 34.0 kWh/year /es RHD 3 rue Glass Glass Transparent 3 Cycle 33.5" 15.13" rue Dial R134a 285.0 2.00.0	0.0" 02.0 lbs3 JL JLC 15 V AC/60 Hz 34.0 kWh/year //es RHD 3 rue Glass Glass Transparent 3 Cycle 33.5" 15.13" rue Dial R134a 285.0	02.0 lbs. 3 UL UC 15 V AC/60 Hz 33.0 kWh/year fes RHD Blass Glass Glass Gransparent Sycle 33.5" 15.13" rue Dial R134a 285.0 20.0 2.6	02.0 lbs. 3 JL JLC 15 V AC/60 Hz 334.0 kWh/year //es RHD Slass Slass Transparent Sycle 33.5° 15.13° True Jial R134a R85.0 18.13° True Jial R134a R85.0	02.0 lbs. 3 JL JLC 15 V AC/60 Hz 334.0 kWh/year //es RHD 3 Slass Slass Stransparent 8 Sycle 13.5° 15.13° True Dial 18134a 1885.0 20.0 20.0 3.66

Summit Appliance Division, Felix Storch, Inc. 770 Garrison Ave • Bronx, NY 10474

Phone: 718-893-3900 • Fax: 718-842-3093

Email: info@summitappliance.com