

PWC
Polaris

OCEANAIRE

Component List
Effective September 1, 2010

MODEL	COOLING CAPACITY BTUH	NEMA PLUG SIZE	VOLTAGE	SHIP WT (lb)	SHIP VOL (cu ft)	ACCESSORIES					
						HOSE KIT			NOZZLE KIT	EVAP PLENUM	DISCHARGE DUCT ADAPTER
						10 FT	25 FT	40 FT			
PWC1211	12000	5-15	115/60/1	130	9	HK-1 3/8"	HK-2 3/8"	HK-5 3/8"	NK-1 2 @ 4"	DEP-10 10"	DDA-6 6"
PWC1811	18000	5-15		170					12	NK-2 2 @ 6"	DEP-12 12"
PWC2412	23950	6-20	208-230/60/1	180	23	HK-3 5/8"	HK-4 5/8"	HK-6 5/8"			
PWC3612	36100	6-20		270					46	NK-3 2 @ 8"	DDA-16 16"
PWC3632		L15-20	208-230/60/3	500							
PWC3634		L16-20	460/60/3		300						
PWC6012	60100	6-30	208-230/60/1	500	46	NK-3 2 @ 8"	DDA-16 16"				
PWC6032		L15-30	208-230/60/3								
PWC6034		L16-20	460/60/3	560							

NOTES:

1. Cooling capacity based on 80°/67°F evaporator inlet and 85° inlet water temperature.
2. Special voltages are available. Consult factory for details/prices.
3. Accessories available for fast user-friendly installation. See Accessory Sheets in catalog for complete information.
4. Hose kits of various lengths are available for supplying water to the unit and to provide drain for the water outlet and condensate pump.
5. Nozzle kit is used in place of the air discharge grille to direct supply air to specific spots. Kit consists of drop-in panel with two flex-duct nozzles.
6. Evaporator plenum is used to direct evaporator return air from a remote location or room to the unit. Flex duct to be supplied separately.
7. Discharge duct adapter is used in place of std. evap. air discharge grille to transform opening to round duct. Flex duct to be supplied separately.
8. See separate price list for special order items and convenience items.

Prices subject to change without notice



OCEANAIRE, INC.

6228 Oakton Street Morton Grove, IL 60053 Phone (847) 583-0311 Fax (847) 583-0312
e-mail: sales@oceanaire-inc.com www.oceanaire-inc.com

R410A Models