DAYTON SPECIFICATIONS

C

GENERAL

Sink is formed of #23 gauge, 300 series, nickel bearing stainless steel. Top mount.

DESIGN FEATURES

Bowl Depth: 5-1/8" (130mm)

Coved Corners: 2-1/4" (57mm) vertical and horizontal radius. Finish: Exposed surfaces are polished to a satin finish. Underside: Undercoated on bottom of bowls to reduce condensation and dampen sound.

SINK PACKAGE

DP211515C Package includes:

- (1) **D11515** sink.
- (1) LKA2475 faucet.

(1) D5018A drain with basket strainer.

OTHER

Drain Opening: 2" (51mm) (D11515, DP211515C), 3-1/2" (89mm) (D11516).

NOTE: Unless otherwise specified, sink is furnished with 2 faucet holes as shown.


Installation Hardware: Included for 3/4" (19mm) countertop. Sink complies with ASME A112.19.3-2008 / CSA B45.4-08.

These sinks are listed by the International Association of Plumbing and Mechanical Officials as meeting the requirements of the Uniform Plumbing Code.


SINK DIMENSIONS (INCHES)*

Model	Overall		Inside Bowl			Cutout in Countertop (1-1/2"(38mm) Radius Corners)		No. of 1-1/4"(32mm) or 1-1/2"(38mm) Dia. Faucet Holes 4"(102mm) Center	Minimum Cabinet
Number	L	W	L	W	D	L	W		Size
DP211515C	15 (381mm)	15 (381mm)	12 (305mm)	10 (254mm)	5-1/8) (130mm)	14-3/8 (365mm)	14-3/8 (365mm)	2	18 (457mm)
D11515	15 (381mm)	15 (381mm)	12 (305mm)	10 (254mm)	5-1/8) (130mm)	14-3/8 (365mm)	14-3/8 (365mm)	1, 2 or 3	18 (457mm)
D11516	15 (381mm)	15 (381mm)	12 (305mm)	10 (254mm)	5-1/8) (130mm)	14-3/8 (365mm)	14-3/8 (365mm)	1, 2 or 3	18 (457mm)

*Length is left to right. Width is front to back.



Bowl Depth is 5-1/8" Model D115152 Illustrated HOLE DRILLING CONFIGURATIONS



In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice.

This specification describes an Elkay product with design, quality and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

