

DA 3466

Built-in ventilation hood with energy-efficient LED lighting and backlit controls for easy use.



- Elegant design slim 23 1/2 (595)Inch extractor canopy
- Efficient filtration- 10-ply stainless steel grease filters
- Safe and easy to clean Miele CleanCover
- Suitable for every home vented or recirculating

EAN: 4002515727034 / material number: 10355910

EAN: 4002515727034 / material number: 10355910	
Construction type	
Built-in ventilation hood	•
Design	
Color	Stainless steel
Operating modes	
Recirculated mode	Convertible
OdorFree charcoal filter (order separately)	DKF13-900
Control panel	
Electronic controls	•
Light-touch controls	_ •
Power levels (number excl. Intensive)	3
Intensive setting	•
Programmable 'Intensive' switch-off	•
Cleaning convenience	
Easy-to-clean CleanCover hood liner	•
Filter system	
Number of dishwasher-safe stainless steel grease filters	1
Lighting	
LED ClearView lighting	_ •
Light intensity in Lx	320
Color temperature in K	3,000
Blower	
Dual-action blower	•
AC motor	•
Air throughput with max. duct diameter in vented	
made (not for external version)	
mode (not for external version)	Values upon request
Air throughput	Values upon request
Air throughput Safety	Values upon request
Air throughput Safety Safety shut-off	Values upon request
Air throughput Safety Safety shut-off Technical data	•
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm)	23 1/2 (595)
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm)	23 1/2 (595) 1 3/8 (34)
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm)	23 1/2 (595) 1 3/8 (34) 10 7/8 (275)
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm)	23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610)
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm)	23 1/2 (595) 1 3/8 (34) 10 7/8 (275)
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm) Minimum height above gas cooktop (max. 12.6 kW total	23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610)
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm) Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm	23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610) 26 (660)
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm) Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm Net weight in lbs. (kg)	23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610) 26 (660) 28 (12.5)
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm) Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm Net weight in lbs. (kg) Length of electrical wire in ft (m)	23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610) 26 (660) 28 (12.5) 4 (1.5)
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm) Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted	23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610) 26 (660) 28 (12.5) 4 (1.5)
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm) Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW	23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610) 26 (660) 28 (12.5) 4 (1.5) 0.36
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm) Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A	23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610) 26 (660) 28 (12.5) 4 (1.5) 0.36 120
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm) Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V	23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610) 26 (660) 28 (12.5) 4 (1.5) 0.36 120 15
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm) Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases	23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610) 26 (660) 28 (12.5) 4 (1.5) 0.36 120 15
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm) Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Installation notes	23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610) 26 (660) 28 (12.5) 4 (1.5) 0.36 120 15
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm) Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Installation notes Vent connection at top	• 23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610) 26 (660) 28 (12.5) 4 (1.5) • 0.36 120 15
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm) Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm Net weight in libs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Installation notes Vent connection at top Diameter of vent connection in in.(mm)	• 23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610) 26 (660) 28 (12.5) 4 (1.5) • 0.36 120 15
Air throughput Safety Safety shut-off Technical data Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Minimum distance above electric cooktops in in.(mm) Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm Net weight in libs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Installation notes Vent connection at top Diameter of vent connection in in.(mm) Standard accessories	• 23 1/2 (595) 1 3/8 (34) 10 7/8 (275) 24 1/8 (610) 26 (660) 28 (12.5) 4 (1.5) • 0.36 120 15


More information at www.MieleUSA.com



DA 3466

Built-in ventilation hood with energy-efficient LED lighting and backlit controls for easy use.





DA 3460, DA 3466 (installation drawing) VG USA

In extraction mode: when measuring for the height of the wall housing unit and the cut-out, account must be taken of any accessories fitted.
 Recirculation mode requires installatiin kit DUU 151.
 Installation with kneeling frame DAR 3000: Please attend differing cabinet height (see installation drawing DAR 3000)