

DA 3496

Built-in ventilation hood  
with energy-efficient LED lighting and backlit controls for easy use.




- Elegant design - slim 35 1/4 (895)Inch extractor canopy
- Efficient filtration- 10-ply stainless steel grease filters
- Safe and easy to clean - Miele CleanCover
- Suitable for every home - vented or recirculating

EAN: 4002515689691 / material number: 10355940

<b>Construction type</b>	
Built-in ventilation hood	•
<b>Design</b>	
Color	Stainless steel
<b>Operating modes</b>	
Recirculated mode	Convertible
OdorFree charcoal filter (order separately)	DKF13-900
<b>Control panel</b>	
Electronic controls	•
Light-touch controls	•
Power levels (number excl. Intensive)	3
Intensive setting	•
Programmable 'Intensive' switch-off	•
<b>Cleaning convenience</b>	
Easy-to-clean CleanCover hood liner	•
<b>Filter system</b>	
Number of dishwasher-safe stainless steel grease filters	2
<b>Lighting</b>	
LED ClearView lighting	•
Light intensity in Lx	320
Color temperature in K	3,000
<b>Blower</b>	
Dual-action blower	•
AC motor	•
<b>Air throughput with max. duct diameter in vented mode (not for external version)</b>	
Air throughput	Values upon request
<b>Safety</b>	
Safety shut-off	•
<b>Technical data</b>	
Canopy width in in.(mm)	35 1/4 (895)
Height of hood canopy in in.(mm)	1 3/8 (34)
Depth of hood canopy in in.(mm)	10 7/8 (275)
Minimum distance above electric cooktops in in.(mm)	24 1/8 (610)
Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm	26 (660)
Net weight in lbs. (kg)	32 (14.5)
Length of electrical wire in ft (m)	4 (1.5)
Standard plug fitted	•
Total connected load in kW	0.36
Voltage in V	120
Fuse rating in A	15
Number of phases	1
<b>Installation notes</b>	
Vent connection at top	•
Diameter of vent connection in in.(mm)	6 (150)
<b>Standard accessories</b>	
Non-return flap	•
Reducer from 150 to 125 mm Ø	•

DA 3496

Built-in ventilation hood  
with energy-efficient LED lighting and backlit controls for easy use.



DA 3490, DA 3496 (installation drawing) VG USA

- 1) Extraction mode
  - 2) Recirculation mode with conversion kit DUU 151
  - 3) Installation with kneeling frame DAR 3000: Please attend differing cabinet height (see installation drawing DAR 3000)
- \* can also be installed in a 600 mm wide unit.