



30" Induction Drop-In Cooktop Specifications

- Product Weight – 48 Lbs.
- Single phase 3- or 4-wire cable, 120/240 or 120/208 Volt, 60 Hertz, fused on both sides of line with ground.
- Connected Load (kW Rating) – 240/208 Volts = 7.4/6.7 kW
- Amps @ 240/208 Volts = 35 Amps
- Always consult local and/or national electric codes.
- Respect critical dimensions as noted for proper installation of cooktop.
- Allow 2" space below armored cable opening to clear electrical cable and allow space for installation of junction box on wall at back of cooktop.
- Overhead cabinetry should not exceed a 13" maximum depth.
- Allow 30" minimum clearance between top of cooktop and bottom of unprotected wood or metal overhead cabinetry.
- The absolute minimum horizontal distance between overhead cabinets installed to either side of the appliance must be no less than the maximum width of the appliance.
- Allow 24" minimum clearance when bottom of wood or metal overhead cabinet is protected by not less than 1/8" flame-retardant millboard covered with not less than No. 28 MGS sheet steel, 0.015" stainless steel, 0.024" aluminum or 0.020" copper.
- Allow 1-1/2" minimum clearance between rear edge of cutout and nearest combustible surface above countertop.
- Allow 7-1/2" minimum clearance from edge of cooktop to nearest combustible wall on either side of unit.
- It is recommended that drawers not be used beneath cooktop.
- To reduce risk of fire when using overhead cabinetry, install range hood that projects horizontally a recommended minimum of 5" beyond bottom of cabinets.

NOTE: Refer to Product Installation Guide for detailed instructions on the web at electroluxusa.com.

Cooking Flexibility

Four induction zones, including a 6", 7", 8" and 10" combine to create a remarkably versatile cook surface for the ultimate flexibility.

Precision Touch Controls

Fifteen preset touch settings provide a level of digital heat control that inspires confidence in even the most particular chef.

Cook Surface Sensors

The Infinite™ Cooking System creates heat only after sensing a pan on the cooking surface. The cook surface diameters respond to both the presence and precise size of a pan. The heat is transferred directly to the pan so the cooktop surface remains cool to the touch.

Enhanced Settings

Power Boost affords rapid heat acceleration, while at the same time reducing energy consumption. For the discerning chef, the Keep Warm Setting allows you to maintain the perfect serving temperature of cooked foods directly on the cook surface. And for complete safety, digital controls enable shut-off at eighteen hours and discretionary lockout from the off position.

30" INDUCTION DROP-IN COOKTOP

Configuration 4 Induction Zones

FEATURES

Black Vitroceramic Glass Surface	Yes
10" Zone – 2400 W/3200W	1
8" Zone – 2200 W/3000W	1
7" Zone – 1800 W/2300W	1
6" Zone – 1200 W/1500W	1
Precision Touch Controls	Yes

SPECIFICATIONS

Cutout Dimensions –	
Height	4-1/2"
Width	29-5/8" min. 29-3/4" max.
Depth	20-3/8" min. 20-1/2" max.
Power Cable Location	Middle Right Rear
Amps @ 240/208 Volts	35 Amps
Connected Load Rating - 240/208 Volts	7.4/6.7 kW
Electrical – Single phase 3- or 4- wire cable, 120/240 V or 120/208 V, 60 Hz, fused on both sides of line with ground.	Required
Armored Electrical Cable	Included
Product Weight	48 Lbs.
Shipping Weight	55 Lbs.
UPC (0-57112-)	09367-3

NOTE: Always consult local and/or national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at electroluxusa.com.

