



36" ELECTRIC DROP-IN COOKTOP **E36EC65ESS**



36" Electric Drop-In Cooktop Specifications

- Product Weight – 44 Lbs.
- Connected Load (kW Rating) – 240/208 Volts = 11.8/8.8 kW
- Single phase 3- or 4-wire cable, 120/240 or 120/208 Volt, 60 Hertz AC only electrical supply with ground required on separate circuit fused on both sides of line.
- Amps @ 240/208 Volts = 50 Amps
- Always consult local and/or national electric codes.
- Allow 2" space below armoured cable opening to clear electrical cable and allow space for installation of junction box on wall at back of cooktop.
- Allow 30" minimum clearance between top of cooktop and bottom of unprotected wood or metal overhead cabinetry.
- Allow 24" minimum clearance when bottom of wood or metal overhead cabinet is protected by not less than 1/8" flame-retardant millboard covered with not less than No. 28 MGS sheet steel, 0.015" stainless steel, 0.024" aluminum or 0.020" copper.
- Allow 2" minimum clearance between rear edge of cutout and nearest combustible surface above countertop.
- Allow 7-1/2" minimum clearance from edge of cooktop to nearest combustible wall on either side of unit.
- It is recommended that drawers not be used beneath cooktop.
- Overhead cabinetry should not exceed a 13" maximum depth.
- To reduce risk of fire when using overhead cabinetry, install range hood that projects horizontally a recommended minimum of 7" beyond bottom of cabinets.

Note: Refer to Product Installation Guide for detailed instructions on the web at www.electroluxusa.com.

Expandable, Flexible Five Burner Configuration

Concentric rings in double and triple elements are clearly marked on the surface. Combinations allow the user to cook with a variety of pan sizes at up to 2700 watts.

Ceramic Smoothtop Glass

Glass cooktop is flat, smooth and easy to clean and maintain.

Center Mount EasySet™ Electronic Controls

The large, professional controls are clearly labeled for quick, easy reading and adjustment.

36" ELECTRIC DROP-IN COOKTOP

Configuration	5 Electric Burners
---------------	--------------------

FEATURES

Black Ceramic Smoothtop Glass Surface	Yes
Large Professional Knobs with Bezel	5
6" to 9" Dual Burner – 1200W/2500W	2
5" to 7" to 9" Expandable Burner – 1000W/1800W/2700W	1
6" Burner – 1200W	2
Hot Surface Indicator Light	5 Positions
Spill Control Cooktop	Yes

SPECIFICATIONS

Power Cable Location	Center
Connected Load Rating - 240/208 Volts	10.16/7.63kW
Electrical – Single phase 3- or 4-wire cable, 120/240 V or 120/208 V, 60 Hz AC only electrical supply with ground on separate circuit fused on both sides of line	Required
Armored Electrical Cable	Included
Product Weight	34 Lbs.
Shipping Weight	38 Lbs.
UPC (0-57112-)	08925-6

NOTE: Always consult local and/or national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at www.electroluxusa.com.

