

EB333610 Single oven Stainless steel Width 36"

Color Variants EB333610 Stainless steel Width 36"

# Included accessories

1 x enamel baking tray. suit. pyrolitic clean.

- 1 x rotary spit.
- 1 x grill shelf.
- 1 x grill tub with grid.
- 1 x pluggable meat probe.

Optional accessories

BA028115

Baking tray, enameled

BA058115

Heating element for baking stone and cast-iron roaster

BA058133

Baking stone

BA090100

Black control knobs for EB 333, set of 2

BS020002

Pizza peel, additional set of 2

GN340230

Non-stick aluminum cast-iron roaster

One-piece front-hinged door with 3 mm precision crafted stainless steel front door panel

Soft door opening and closing system

Diagonally positioned light sources for optimal interior lighting Pyrolytic self-cleaning Universal heating system with 17 heating modes, with meat probe, rotisserie spit and baking stone operation

Convection fan rotates in both directions for ideal heat distribution TFT touch display

Panel-free appliance with control module behind glass Electronic precision temperature

control from 85° F - 550° F 3.6 cu.ft. net volume

#### Cooking modes

Convection.

Economy convection.

Top + bottom heat.

Top + 1/3 bottom heat.

Top heat.

1/3 top + bottom heat.

Bottom heat.

Convection + bottom heat.

Convection + 1/3 bottom heat.

Convection broiling.

Broiling.

Compact grill.

Baking stone operation.

Roaster function.

Dough proofing.

Defrosting.

Detrosting. Keeping warm.

# Operation

Rotary knobs and TFT touch display operation.

Clear text display in 25 languages.

Option to save individual recipes (incl. meat probe)

Information key with use indicators. Front-hinged door with 90° door opening angle.

# Features

Meat probe with automatic shut-off function.

Rotisserie spit.

Baking stone outlet.

Actual temperature display. Super-quick preheating.

Timer functions: cooking time, switchoff time, short-term timer, stopwatch.

Sabbath mode. 60 W halogen light on top.

2 x 10 W halogen light on the side. Enamelled side shelf supports with 3 rack levels, pyrolytic-safe.

# Safety

Thermally insulated door with quintuple glazing.

Child lock.

Safety lock.
Cooled door housing with temperature protection.

# Cleaning

Pyrolytic self-cleaning. Gaggenau Clean-Enamel. Heated air cleaning catalyst.

# Planning notes

The door panel surface of the appliance extends 1 9/16" (40 mm) from the furniture cavity.

#### **Product Features**

#### Cooking mode

Baking stone function, Bottom heat, Bottom heating, 1/3 top heat., Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, Top heating, 1/3 bottom heat, warming

Integrated Cleaning system

Self Clean

Interior Lights - primary cavity

Pull-out system

Accessory

Timer settings

Alarm, Off, On, timer

## Included accessories

1 x enamel baking tray,suit. pyrolitic clean, 1 x rotary spit, 1 x grill shelf, 1 x grill tub with grid, 1 x pluggable meat probe

Bake Element Wattages primary cavity (W)

(47)

Broil Element Wattages primary cavity

(W) 4250

Convection Element Wattages primary

cavity (W) 2070

Microwave Wattages (W)

Drawer wattage (W)

# Consumption and connection features

UPC code

825225922544

Product color

Stainless steel

Alternative colors available

Energy source

Watts (W)

Walls (V

Current (A)

25

Volts (V) 208/220-240

Frequency (Hz)

60

Approval certificates

Power Cord Length

47 1/4

Plug type fixed connection

Required cutout size (HxWxD) (in)

18 11/16 x 33 7/8 x 22 1/16

Product packaging dimensions (HxWxD) (in)

27 9/16 x 39 3/4 x 28 15/16

Net weight (lbs)

Gross weight (lbs)

206

2017-04-06 Page 1 The outer edge of the door handle extends 3 9/16" (90 mm) from the furniture cavity.

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 19/32" (15 mm). The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 21 5/8" (550 mm) installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.


Plan a power outlet outside of the cutout niche.


## Rating

Total rating 5.9 kW.
Total Amps: 25 A.
208 / 220 - 240 V / 60 Hz
Connection cable 47 1/4 without plug (hardwire required).



EB333610 Single oven Stainless steel Width 36" 2017-04-06 Page 2





# **GAGGENAU**