BREAN Elite

Introducing the E60000 & E64000 Series

True professional style and performance has never been easier to bring home.

Selecting the right professional style range hood just became easier. Broan introduces the E64000 and E60000 range hoods, in 10" under-cabinet and 18" wall-mount versions. These new models come with integrated internal blowers or dedicated external blower capability. Styling is fresh and modern, yet designed to easily complement popular pro-style cooking products. Both embody professional features such as powerful blowers, baffle filters, brilliant halogen lighting and variable speed controls. And while you won't see this feature it is hard to miss the quiet operation—two Sones or less at normal speed. To carry the professional theme even further, select the optional stainless steel backsplash with adjustable shelving. When you want professional style and performance, trust Broan to cover every detail.





Above: E60000 with optional 12" soffit flue

Right: E60000 with non-duct recirculating kit





Above:

E64000 in ducted installation (shown with custom backsplash)

Left:

E64000 with non-duct recirculating kit (shown with custom backsplash)





E60000 Series. Take professional style to new heights.


- 18" wall-mount design
- Brushed stainless steel finish
- 30", 36", 42" and 48" widths, 24" depth
- 600 CFM internal blower is standard on 30" and 36" models
- 1200 CFM internal blower is standard on 42" and 48" models
- Dedicated models in all widths for use with external blower options—choice of eight, from 280-1500 CFM
- Non-duct kit option available for all widths
- Bright halogen lighting; Two 50-watt bulbs in 30" and 36" widths, Three 50-watt bulbs in 42" and 48" widths (purchase bulbs separately)
- Pro-style, dishwasher-safe baffle filters with removable grease drip rail
- Variable speed control remembers last setting—blue LED power-on indicator light
- decorative 12" soffit flue
- Designed to duct out of the hood shell in either horizontal or vertical direction with any blower configuration

E64000 Series. Professional style that fits under any cabinet.

- 10" under-cabinet design
- · Brushed stainless steel finish
- 30", 36", 42" and 48" widths, 22" depth
- 600 CFM internal blower is standard on all models
- 1200 CFM blower also available in 48" model
- Dedicated models in all widths for use with external blower options—choice of eight, from 280-1500 CFM
- Non-duct kit option available for all widths
- Bright halogen lighting; Two 50-watt bulbs in 30" and 36" widths, Three 50-watt bulbs in 42" and 48" widths (purchase bulbs separately)
- Pro-style, dishwasher-safe baffle filters with removable grease drip rail
- Variable speed control remembers last setting—blue LED power-on indicator light
- Heat Sentry[™] detects excessive heat and adjusts blower speed automatically
- Optional pro-style backsplash
- Designed to duct out of the hood shell in either horizontal or vertical direction with internal blowers. External blowers duct vertically

Heat Sentry[™] detects excessive heat and adjusts blower speed automatically · Optional pro-style backsplash and

Features



Dishwasher-safe baffle filters feature handles for convenient removal.



Rotary controls for two-level lighting and variable blower speeds enable the user to choose operating preferences.

Optional Accessories



A non-duct kit may be used to recirculate filtered air back into the kitchen if ducting is not practical



A stainless steel backsplash with integral shelving completes the professional look.

www.Broan.com Broan-NuTone, LLC 926 W. State Street, Hartford, WI 53027 800-558-1711 Canada 877-896-1119

Series	Width	Internal Blower** 600 CFM Duct 3-1/4"x10"	Internal Blower** 1200 CFM Duct 4-1/2" x 18"	External Blower** Capable Duct 10" Rd	Lamps (Purchase Seperately)	Max Amps*	Sones at Normal Speed*	Optional Non-duct Kit	Optional 12" Soffit Flue Cover	Optional Backsplash
E64	30"	E6430SS		E64E30SS	2 - 50W GU10	5.5	1.5 max	ANKE60302SS		RMP3004
	36"	E6436SS		E64E36SS	2 - 50W GU10	5.5	1.5 max	ANKE60362SS		RMP3604
	42"	E6442SS		E64E42SS	3 - 50W GU10	6.0	1.5 max	ANKE60422SS		RMP4204
	48"	E6448SS	E6448TSS	E64E48SS	3 – 50W GU10	9.0	2.0 max	ANKE60482SS		RMP4804
E60	30"	E6030SS		E60E30SS	2 – 50W GU10	5.5	1.5 max	ANKE60302SS	AEE60302SS	RMP3004
	36"	E6036SS		E60E36SS	2 – 50W GU10	5.5	1.5 max	ANKE60362SS	AEE60362SS	RMP3604
	42"		E6042TSS	E60E42SS	3 – 50W GU10	9.0	2.0 max	ANKE60422SS	AEE60422SS	RMP4204
	48"		E6048TSS	E60E48SS	3 - 50W GU10	9.0	2.0 max	ANKE60482SS	AEE60482SS	RMP4804





^{*} Sones at high speed for Internal 600 – 13.5 max; Internal 1200 – 14.5 max

** Duct adapter & damper is included with the Internal blowers: External blower capable models include the 332KR rough-in kit

120V 60Hz