

FULGOR
MILANO

600 Series 36" Induction Range

F6PIR365S1



Series

Size
Main Colour
Logo
Stainless Steel Aesthetics

600
FULL ELECTRIC
36"
SS
●
Professional

Cooktop

Type

INDUCTION

Cooking Surface
Knobs

Ceramic Glass
●

Induction Special Features

Pot Detection System
Child lock function
Cooling fan system
Failure Codes indication

●
●
●
●

Induction Control Features

Knob for power setting (illuminated)
Power levels
Digital display for power level indication
Melting Function 113°F / 45°C (inside the pot 108°F / 42°C)
Warming Function 158°F / 70°C (inside the pot 149°F / 65°C)
Booster/Fast boil function for each zone
Heat up time automatic
Residual heat indication

●
1 to 9
●
●
●
●
●
●

Cooking Zones

5

Front Left

Inductor 9" (230mm)

Power L9
Booster

2300W
3700W

Rear Left

Inductor 7" (180mm)

Power L9
Booster

1850W
3000W

Middle dual circuit

Inductor 11" (280mm)

Power L9
Booster

3000W
5500W

Middle single circuit

Inductor 7" (180mm)

Power L9
Booster

1850W
2600W

Front Right

Inductor 9" (230mm)

Power L9
Booster

2300W
3700W

Rear Right

Inductor 7" (180mm)

Power L9
Booster

1850W
3000W

FULGOR

MILANO

Oven

Type		ELECTRIC PIRO	
Oven Type	Multifunction 2 Fans (True Euro Convection)		
Temperature Regulation	Electronic (max temp. 550°F/290°C)		
Functions			
Pyrolitic Self-Clean with automatic door latch			•
True European Convection Bake (Multi level)			•
Convection Broil			•
Convection Roast			•
Pizza (Lower Convection)			•
Bake			•
Broil			•
Dehydrate			•
Thaw (Defrost)			•
Proof (Warm)			•
Keep warm (Warm Plus)			•
Oven Lights			•
Fast Preheat			•
Control Panel			
Control type	HAWK3TC - Electronic		
Clock Display	White LED		
Temperature Display	White LED		
Function Display	White LED		
Commands	6 Heavy Duty Knobs / 6 Touch Keys		
Language	English		
Electric Oven Features			
Preset/Last used temperature memory			•
Preheat bar (25%, 50%, 75%, 100%)			•
Automatic Fast Preheat			•
Child Door Lock			•
Commands Lock			•
Sabbath mode			•
12/24 hour clock format			•
°C/°F			•
Oven Door(s)			
Oven Glass Window	Deep Embossed Window		
Door Cooling System	4 Pane Heat Resistant Glass		
Soft closing system			•
Door Hinges	Heavy Duty Steady Tilt		
Handle Style	Stainless Steel Tube d30mm, Pro Style		
Oven Cavity			
Gross Capacity (cuft)			5.7
Usable Capacity (cuft)			4.9
Cavity Enamel Colour			Black
Rack Positions			6
Oven Lights			3x20W Halogen
Heating Element			
Broil Upper Heating Element			3500 W (240V)
Upper Auxiliary Element Wattage			1032W (240V)
Concealed Bake Lower Heating Element			3000 W (240V)
Convection Element Wattage			2x1300 W (240V)
Oven Accessories			
Chromed racks			2
Enameled Grill set (basin + anti splash)			1
Telescopic chromed rack			1
Meat probe			1
Dimensions			
Overall dim - width			35 3/4" (910mm)

FULGOR

MILANO

Height min/max	36 3/8" (925mm) / 38 1/2" (977mm)
Overall dim - depth	29 3/4" (756mm)
Power / Ratings (208 / 240 V, 60 Hz)	
KW/Amps rating at 120-240V, 60Hz	14.6KW - 61A
KW/Amps rating at 120-208V, 60Hz	13.3kW - 63A
Cable + Plug	Nema 14-50P
INSTRUCTIONS FOR USE	
Use & Care Manual	EN, SP, FR
Installation Manual	EN, SP, FR