

15"W. NUGGET ICE MACHINE

Your favorite ice within arm's reach





Unit shown with optional Viking Professional stainless steel door panel

Gravity drain or built-in drain pump models available



15"W. NUGGET ICE MACHINE FEATURES

Constant Supply of Soft and Chewable Ice

- Soft and chewable ice assumes the flavor of any beverage to enhance your overall experience
- 80 pounds of ice production in 24 hours provides enough chewable ice for all of your entertaining needs
- Ultrasonic bin level sensor automatically stops ice production when the bin is full
- Ice bin stores up to 26 pounds of ice



Quiet and Energy Efficient

- The soft ice form aids in ultra-quiet operation when dropping into bin
- Uses 40% less energy and more than 50% less water than comparable ice machine models
- Self-closing door helps reduce energy costs
- Energy efficient LED light illuminates bin interior for visibility with minimal energy consumption

Easy Maintenance and Cleanup

- User-friendly electronic control panel clearly displays ice production status and maintenance needs
- LED indicator light illuminates when ice machine is running and alerts of no-water condition
- No need to disconnect or uninstall machine when cleaning



Unmatched Installation Flexibility

- Available with gravity drain or built-in drain pump, eliminating need for floor drain
- Ships with unfinished door front, accommodating either an optional right or left hand Viking stainless steel front panel or a custom wood panel
- Tru-Flush™ Design allows flush-to-cabinet installation
- Fully finished stainless steel exterior cabinet allows for a finished look in freestanding applications
- Approved for both indoor and outdoor use

The Industry's Best and Most Comprehensive Warranty

- 3-year full warranty complete unit
- 6-year full warranty sealed system
- 90-day full cosmetic parts such as glass, painted items, and decorative items



- Lifetime limited stainless steel exterior
- 12-year limited sealed system

SPECIFICATIONS*

15"W. Nugget Ice Machine		
Description	FGNI515	FPNI515
Overall width	14-7/8" (37.8 cm)	
Overall height	33-7/8" (86.0 cm) min. to 34-7/8" (88.6 cm) max.	
Overall depth from rear (without door panel) (with door panel) (with door handle)	22" (55.9 cm) 22-3/4" (57.8 cm) 25-1/4" (64.1 cm)	
Cutout width	15" (38.1 cm)	
Cutout height	34-1/4" (86.4 cm) min. to 35-1/4" (89.5 cm) max.	
Cutout depth	24" (61.0 cm)	
Electrical requirements	115V/60 Hz, 15 amp dedicated circuit 6′ 3-wire cord attached to product	
Maximum amp usage	5.0 amps	
Inlet water requirement	1/4" OD copper tubing inlet waterline 20 psi min. to 80 psi max. 50°F (10°C) min. to 100°F (38°C) max.	
Drain requirements	5/8" ID x 7/8" OD plastic tubing required	3/8" ID x 10' plastic tubing supplied
Temperature requirements	50°F (10°C) min. to 100° (38°C) max.	
Maximum storage capacity	26 lbs.	
Approximate shipping weight	124 lbs. (56.2 kg)	129 lbs. (58.5 kg)



For detailed product information, model numbers, or to request a quote call 1-888-845-4641 or visit vikingrange.com