

FS30LMED2



26.5" x 18.5" x 17.75" (H x W x D)

Compact medical/scientific all-freezer with digital thermostat, NIST calibrated thermometer/alarm, and front lock

Highlights:

Specially designed and featured to meet the CDC and VFC's guidelines for safe vaccine storage

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Assembled in the USA from domestic and imported components

Product Features:

| | |
|-------------------------------------|---|
| Reliable temperature stability | Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions |
| Digital thermostat | Electronic controls for more precise temperature management, with temperature readout and controls externally located for added convenience |
| High/low temperature alarm | Audible alarm sounds if the interior temperature rises or falls out of set range |
| NIST calibrated temperature display | Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button |
| Buffered temperature probe | Thermometer probe is encased in a glycol-filled bottle to maintain temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines |
| Factory installed lock | Keyed lock for convenient security, with two keys included |
| Manual defrost | Static cooling system for reduced temperature fluctuations |
| Hospital grade cord and plug | Secure three-pronged cord for added unit safety |
| 3/8" access port | Unit comes with a factory installed probe hole for users to connect their own monitoring equipment |

FS30LMED2 Specifications:

| Overview | |
|----------------------------|--------------------|
| Height of Cabinet | 26.5" (67 cm) |
| Width | 18.5" (47 cm) |
| Depth | 17.75" (45 cm) |
| Depth with door at 90° | 34.5" (88 cm) |
| Capacity | 1.8 cu.ft. (51 L) |
| Defrost Type | Manual |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 0.8 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 50.0 lbs. (23 kg) |
| Shipping Weight | 53.0 lbs. (24 kg) |
| Estimated Time to Ship | 5 to 7 days |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| Freezer | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Interior Height | 18.5" (47 cm) |
| Interior Width | 13.5" (34 cm) |
| Interior Depth | 13.0" (33 cm) |
| Shelf Type | Wire |
| Shelf Qty | 2 |
| Thermostat Type | Digital |
| Refrigerant Type | R134a |
| Refrigerant Amount | 0.85 oz. |
| High Side PSI | 108.0 |
| Low Side PSI | 58.0 |
| Level Legs | 2 |
| Compressor Step Height | 7.75" (20 cm) |
| Compressor Step Width | 13.5" (34 cm) |
| Compressor Step Depth | 6.0" (15 cm) |
| Temperature Range | -20 to -15°C |

