24" C-SERIES BEVERAGE CENTER

HC24BB-3 | 24" INDOOR MODEL







Solid Door Model

Glass Door Model

GENERAL C-SERIES FEATURES

- Zero-clearance hinging allows for abutment with surrounding cabinetry
- 525 Btu commercial-grade compressor
- Front-vented, RAPIDcool forced-air refrigeration system
- · Commercial-grade stainless steel interior
- *Industry Exclusive* convertible door design allows all doors the ability to be converted to wood overlay from stainless steel
- *Industry Exclusive* adjustable, full-extension pull-out shelves (drawer models excluded)
- Stainless-steel ball-bearing glides provide smooth movement of shelves
- Low E, UV-coated glass provides industry leading insulation and protection.

- Digital temperature control
- Interior light
- Optional door locks and Industry-Exclusive drawer locks (factory installed)
- Stacking kit available
- · Indoor and outdoor models available
- Also available 24" Indoor Refrigerator and Wine Reserve, 24" Outdoor Refrigerator
- 5.2 cubic feet of capacity
- Industry Best Three Year Warranty plus additional three years on sealed system

HC24BB FEATURES

- Available with solid stainless steel door, solid wood overlay door, stainless steel glass door or wood overlay glass door
- Black vinyl-clad exterior
- Includes two (2) full-extension wine shelves and one (1) pull-out shelf
- Beverage Center temperature 33°- 48°F

Form No.HC24B-3 Rev. 09.19.2014

PRODUCT SPECIFICATIONS

Overall Width 23-7/8" (60.64 cm.) HC24BB-3-1L* Solid stainless steel door, hinge left HC24BB-3-2L* Solid wood overlay door, hinge left **Overall Height** 34-1/4" (86.96 cm.) HC24BB-3-3L* Stainless steel glass door, hinge left **Overall Depth** 24" (60.96 cm.) HC24BB-3-4L* Wood overlay glass door, hinge left **Opening Width** 24" (60.96 cm.) **Opening Height** 34-3/8" (87.31 cm.) * Also available hinge right **Opening Depth** 24" (60.96 cm.) **Refrigerated Volume** 5.2 cu. ft. **Door Swing Clearance** 25" (63.5 cm.) minimum Electrical 115V, 60Hz., 1 Phase, 2.3 amps Plumbing None Required **Shipping Weight** 195 lbs (88.45 kg.) **Annual Energy** 274 kWh (solid door) Consumption 305 kWh (glass door) 50" Area in which electrical outlet must be located. Power cord 6-5/8" off floor.* 7 9/16" 6 1/4" 18 3/16" 20' 1 1/2" Min. 11 7/8 clearance from a corner to acheive 90° door swing. *- Leg leveler can add 3/4" to these dimensions when fully extended. 90° Swing required for pull-out shelf 24 15/16" Min. clearance for door swing. learance 24" 1 1/2" Value may (with $\pm 1/16$ " tolerance) change due to a Value may change custom pull. with a wood overlay door. 18 3/16" 23 7/8" 20' ช ช ช ช ช ช ช 000000 23 1/16" 23 1/16" 26 9/16" 26 9/16" 2" Shelf *34 5/16" adiustability. 4 **c**h 3 1/2" 3 1/2" 4 1/4" Lowest shelf location. - 11 7/8" 🗕 6 1/4" *3 7/8" 17/8" 22 1/8

INDOOR MODELS