

Fast and easy meals on weekdays.
Slow and complex on weekends.



Gas, Electric, Dual Fuel Models

Siemens xTronic® ranges are available in gas, electric or dual fuel (gas cooktop and electric oven). Each model has its advantages, but for the true culinary enthusiast, the dual fuel model provides ultimate control.

Better Convection Oven Cooking

By adding a third heating element and by precisely controlling convection airflow, the Siemens threeD Surround Convection® system makes convection cooking even more efficient. In fact, it cooks up to 25% faster than non-convection cooking.

Easy Cooking

Siemens xTronic® ranges make cooking easy with a large oven cavity and up to 11 pre-programmed cook modes, including Proof, Dehydrate and Sabbath modes. Gas and dual fuel models feature continuous cooktop grates and a powerful 16,000 – 400 BTU gas burner, while the electric model offers a 2700W high-power heating element and front controls that maximize cooking surface width.

Easy Cleaning

A two-hour convection self-cleaning feature makes oven cleaning fast and easy. Gas and dual fuel models add sealed burners and a one-piece stainless steel cooktop, while the electric model offers a seamless cooktop.

German Engineering

No detail is overlooked in the construction of a Siemens xTronic® range. Each one is engineered for durability and performance.



xTronic® Convection Ranges

The future moving in.

SIEMENS

xTronic® Convection Ranges Specifications




Gas Range HG2528UC



Dual Fuel Range HD2528U



Electric Range HE2528U



Dimensions

A	21-5/8"	D	47-1/2"
B	25-5/8"	E	29-15/16"
C	36"		



Range Ventilation/Microwave Available Separately HF36V305

	xTronic® Convection Gas Range All Stainless Steel HG2528UC (US and Canada)	xTronic® Convection Dual Fuel Range All Stainless Steel HD2528U (US)	xTronic® Convection Electric Range All Stainless Steel HE2528U (US)
Cooktop Performance			
versaTemp® 16,000 – 400 BTU Burner	■	■	
Size-Adaptable Cooktop Elements			1 Dual, 1 Triple
powerHeat Element			2700W
Cooktop Convenience			
Offset Right Rear Burner	■	■	
xxL Professional Continuous Grates™	■	■	
Sealed Burners for Easy Cleaning	■	■	
Front Controls (Max. Cooktop Width)			■
Hot Surface Indicator Lights			■
Cooktop Design			
One-Piece Stainless Steel Top	■	■	
Low Profile to Countertop	■	■	
Stainless Steel-Framed Cooktop			■
Oven Performance			
threeD Surround Convection® with Third Heating Element	■	■	■
Oven Cavity Capacity (cu. ft.)	5.1	4.6	4.6
Precision Temperature Monitoring	■	■	■
8-Pass Concealed Bake Element		■	■
10-Pass Broil Element with Reflector Shield		■	■
Broiler Pan	■	■	■
Oven Cooking Modes			
Total Pre-Programmed Cook Modes	10	11	11
Bake	■	■	■
Broil	■	■	■
Convection Conversion	■	■	■
Auto Convection Bake	■	■	■
Convection Broil		■	■
Convection Roast	■	■	■
Proof	■	■	■
Keep Warm	■	■	■
Dehydrate	■	■	■
Sabbath	■	■	■
Temperature Probe	■	■	■
Oven Convenience			
diaLogic™ Oven Control Dial	■	■	■
Touch-Through-Glass Controls	■	■	■
activeClean™ Convection Self-Cleaning	■	■	■
Standard Racks	2	2	2
Telescopic Extension Rack	1	1	1
Rack Positions	6	6	6
Warming Drawer with Sabbath Mode, 1.3 cu. ft.	■	■	■
Automatic Oven Lights	2	2	2
Natural Gas/Liquid Propane Convertible Kit	■	■	
Oven Design			
Extra-Wide Oven Windows	■	■	■
Stainless Steel Control Panel	■	■	■
Technical			
Burner	LF 9,100 BTU	LF 9,100 BTU	
Burner	LR 12,500 BTU	LR 12,500 BTU	
Burner	RR 5,500 BTU with low simmer	RR 5,500 BTU with low simmer	
Burner	RF 16,000 – 400 BTU	RF 16,000 – 400 BTU	
120 volts, 3-wire, 60 Hz, 15A	■		
Dual Rated 208/240 Volts, 4-Wire, 60 Hz, 30A		■	
Dual Rated 208/240 Volts, 4-Wire, 60 Hz, 40A			■
quickStart™ Heating Element			LF 6" 1200W
quickStart™ Heating Element			LR Triple 5"7"9" 2500W
quickStart™ Heating Element			RR 6" 1200W
quickStart™ Heating Element			RF Dual 9"12" 2700W

1-888-4-SIEMENS • In the US: siemens-home.com

©2007 BSH Home Appliances Corporation. All rights reserved. Specifications subject to change without notice.

Ranges are UL approved. For immediate critical installation dimensions by fax, use your handset and call 775-833-3600.

Warranty: BSH warrants that its range products are free from defects in materials and workmanship for a period of 1 year for labor and 1 year for parts. Certain limitations apply. See Manufacturer's Limited Warranty for details. SE_PH_MPC_1_001