



Eco-Friendly
Refrigerant



Remote with
LED Display



Remote without
LED Display

ELECTRONIC CONTROLLED WINDOW AIR CONDITIONER

PMTS



Dripless
Technology



Energy Saver
Function



Sleep
Mode



24 Hour
Timer



Clean Filter
Indicator



LED
Display



4 Way
Air Direction



Auto Restart



3 Cooling Speeds
3 Fan-Only Speeds

PMTS (Personal Mapping Temperature Sensor)




Includes a Deluxe Remote control with large LED display! There is no need to strain your eyes to view the temperature settings on your unit. The "Personal Mapping Temperature Sensor" will sense the temperature from where the remote control is located. The Air conditioner will continue to cool until your desired temperature has reached the area (in the room) where the remote control is located.

Quality Performance

Save money and stay cool with the Impecca Preferred Air Conditioning unit. Its 15K/18K/25K Cooling BTU/h, operating using energy-efficient technology, will easily cool a room with up to 7000/1,000/1,500 square feet. Guide the air flow as you like with 4-way air direction. In the case of a power outage, the Impecca Preferred Air Conditioner will memorize and resume at your temperature settings when power is restored.

SPECS

Model		IWA15KSFP	IWA18KS	IWA25KS
Performance	Cooling Capacity (BTU/hr)	15100	18500/18200	25000/24700
	Application area (Sq. Feet)	550-700	700-1000	1400-1500
	EER	10.7	10.7	9.4
	Energy Star	Yes	Yes	Yes
	Air Flow (m3/h) (High)	710	760	920
Electrical Ratings	Voltage	115	230/208	230/208
	Watts	1410	1730/1700	2660/2630
	Amps	12	7.7/8.3	12.0/12.8
	Cord Length (Ft)	6.4	6.4	6.4
Features	PMTS	Yes	No	No
	Dry Mode	Yes	Yes	Yes
	Active Carbon Filter	No	No	No
	Electronic Control / LED Display	Yes	Yes	Yes
	Remote Control	Yes - w/LED Display	Yes - w/o Display	Yes - w/o LED Display
	Cool / Fan Speeds	3 / 3	3 / 3	3 / 3
	Auto Restart	Yes	Yes	Yes
	Timer	Yes - 24 Hour	Yes - 24 Hour	Yes - 24 Hour
	Clean Filter Indicator	Yes	Yes	Yes
	Energy Saver Mode	Yes	Yes	Yes
	Sleep Mode	Yes	Yes	Yes
	Air Direction	4 Way	4 Way	4 Way
	Moisture Removal (L/hr)	0.9	1.1	1.1
	Indoor noise level dB(A) (Low)	53	54	54
	Refrigerant type	R410A	R410A	R410A
	Chassis Type	Slide-Out	Slide-Out	Slide-Out
Dimensions	Unit Width	23.62"	23.62"	26.5"
	Unit Depth	25.39"	25.39"	25.47"
	Unit Height	17.91"	17.91"	18.62"
	Carton Width	25.95"	25.98"	29.52"
	Carton Depth	29.92"	29.92"	31.26"
	Carton Height	18.90"	18.90"	20.08"
Weight	Net / Gross (Lbs.)	99.2 / 111.33	114.64/ 127.87	122.35 / 136.69
Loading Q'ty	Pallet	4	4	4
	Container (40'HQ)	270	270	225



IN HOME SERVICE
2YR PARTS & LABOR
5YR SEALED SYSTEM

INSTALLATION KIT INCLUDED!
(tools not included)