

KFMC 3642 L

MasterCool™ fridge-freezer

MasterFresh Pro | AirClean system | IceMaker | M Touch Pro | ColdSteel



- Food stays fresh for up to 5 times longer – MasterFresh Pro
- Everything in full view at all times – Cameras in the refrigerator
- Fresh supplies without unpleasant odors – Longlife AirClean System
- Sophisticated interior design – ColdSteel

EAN: 4002516768715 / Material number: 12489490 /  
Old Material Number: 38364210USA

General information	
Model number	KFMC 3642 L
Manufacturer material number	12489490
EAN number	4002516768715
Class	Platinum
Appliance category	
Fridge-freezer	•
Design	
Built-in	•
Built-in integrated	•
Door hinge side	Left
Convertible hinging	•
Can be installed side-by-side	•
Design	
Design option	Compatible with furniture fronts
Lighting	BrilliantLight
SmartLight	•
User convenience	
Networking with Miele@home	•
Electronic temperature display and control	M Touch Pro
Sabbath mode	•
Freshness system	MasterFresh Pro + DailyFresh ExtraCool
Longlife AirClean System	•
DynaCool	•
Holiday mode	•
NoFrost	•
DuplexCool Pro	•
SoftClose door closing damper	•
SelfClose	•
Number of IceMakers with plumbed water connection	1
IceMaker with mains water connection	•
FullAccess	•
EasyClean	•
MaxLoad hinge	•
Control	
Precise adjustment	Fridge and freezer temperature
Fridge compartment can be switched off	No
Independent temperature control of fridge and freezer compartments	Yes
SuperCool&AirClean	•
SuperFrost	•
No. of temperature zones	3
Eco mode	•
QuickIce	•
Fridge/fridge zone	
Height-adjustable, full-width tempered glass shelves	2

KFMC 3642 L

MasterCool™ fridge-freezer

MasterFresh Pro | AirClean system | IceMaker | M Touch Pro | ColdSteel




EAN: 4002516768715 / Material number: 12489490 /  
Old Material Number: 38364210USA

Number of VeggieBoxes	1
No. of PerfectFresh drawers	1
Door rack for tins	2
Inner door racks for bottles	1
<b>Freezer/freezer zone</b>	
Number of freezer baskets	3
of which on telescopic rails	2
<b>Efficiency and sustainability</b>	
Energy Star Qualified	•
<b>Safety</b>	
Spill-proof glass shelves	•
Acoustic door alarm	•
Acoustic temperature alarm, freezer section	•
<b>Technical data</b>	
Niche width in inches (mm), min.	36 (914)
Niche width in inches (mm), max.	36 (914)
Niche height in inches (mm), min.	84 1/8 (2134)
Niche height in inches (mm), max.	84 1/8 (2134)
Niche depth in in.(mm)	25 (635)
Appliance width in in.(mm)	35 1/4 (894)
Appliance height in in.(mm)	83 5/8 (2123)
Appliance depth in in.(mm)	24 (608)
Weight in lbs.(kg)	483 (219.0)
Type of mounting	Fixed door
Maximum fridge compartment door front weight in lbs. (kg)	133 (60)
Maximum freezer compartment door front weight in lbs. (kg)	38 (17)
Total usable capacity in cu. ft. (l)	20.2 (572)
Current consumption in milliampere (mA)	4000
Voltage in V	110-120
Fuse rating in A	10
Number of phases	1
Frequency in Hz	60
Wire length in ft (m)	9 (3.0)
Replacing bulbs	Customer Service
<b>Standard accessories</b>	
Ice scoop	•

## KFMC 3642 L


MasterCool™ fridge-freezer

MasterFresh Pro | AirClean system | IceMaker | M Touch Pro | ColdSteel




KFMC3642R, KFMC3642L, MasterCool III, stainless steel frame, with stainless steel front, installation

View from the front, 1. Mains connection cable, L = 3000 mm (118 inch), 2. Water connection L = 1800 mm (70 inch)




KFMC3642R, KFMC3842L, KFMC3844R, KFMC3844L, MasterCool III, installation, panel ready


Information for KFMC 3642 L + R (US/CD) only, View from the front, 1. Mains connection cable, L = 3000 mm (118 inch), 2. Water connection L = 1800 mm (70 inch), Information for KFMC 3844 L + R (EU), 1. Mains connection cable, L = 3000 mm, 2. Water connection L = 1800 mm



KFMC3642R, KFMC3642L, MasterCool III, stainless steel frame, with stainless steel front, integration




KFMC3642R, KFMC3842L, KFMC3844R, KFMC3844L, MasterCool III, integration, panel ready




KFMC3642R, KFMC3842L, KFMC3844R, KFMC3844L, MasterCool III, front view


1. 47 kg / 103,6 lbs, 2. 14 kg / 30,8 lbs




KFMC3632R+L, KFMC3642R+L, KFMC3836R+L, KFMC3858FD, MasterCool III, frame neutral, installation



KFMC3632R+L, KFMC3642R+L, KFMC3836R+L, KFMC3834R+L, KFMC3858FD, MasterCool III, hinge clearance, installation



KFMC3632R+L, KFMC3642R+L, KFMC3836R+L, KFMC3834R+L, KFMC3858FD, MasterCool III, Side-view bottom, installation




KFMC3642R, KFMC3642L, MasterCool III, stainless steel frame, with stainless steel front, top view

KFMC 3642 L

MasterCool™ fridge-freezer

MasterFresh Pro | AirClean system | IceMaker | M Touch Pro | ColdSteel



KFMC3642R, KFMC3642L, KFMC3844R,  
KFMC3844L, MasterCool III, panel ready, top view