

## KM 5627 208V

## Electric cooktop

36 1/8 (915) wide for extremely convenient cooking.



- Easy and direct controls operation via knob controls
- Attractive design 36 1/8 (915)Inch wide with stainless steel frame
- Versatile 5 cooking zonesSafe residual heat indicator for every cooking zone

Type of heating	
Fuel type	Electrical
Construction type	2.00011001
Independent of oven	•
Design	
Elegant glass ceramic surface	•
Ceramic surface color	Black
Print design	Basalt grey decor
All-round stainless steel frame	•
Ring features	
No. of rings	5
Ring	
Position	front left
Туре	Variable cooking zone
Size in inches (mm)	Ø 180 / Ø 230
Max. rating in W	1600/2500
Position	rear left
Туре	Single-circuit ring
Size in inches (mm)	Ø 145
Max. rating in W	1200
Position	rear center
Туре	Variable cooking zone
Size in inches (mm)	120/180 mm
Max. rating in W	700/1800
Position	right
Туре	Variable cooking zone
Size in inches (mm)	Ø 210 / Ø 270
Max. rating in W	2000/2700
Position	front center
Туре	Variable cooking zone
Size in inches (mm)	Ø 120 / Ø 180
Max. rating in W	700/1800
Control panel	
Operation via touchpad sensors	Knob
Operation via knobs	•
Display color	Red
Extended ring area	•
Efficiency and sustainability	
Residual heat utilization	•
Cleaning convenience	
Easy to clean ceramic surface	•
Safety	
Overheating protection	•

More information at www.MieleUSA.com



## KM 5627 208V

Electric cooktop 36 1/8 (915) wide for extremely convenient cooking.




Technical data	
Dimensions in in. (width)	36 1/8 (915)
Dimensions (height) in in.(mm)	3 1/4 (81)
Dimensions (depth) in in.(mm)	21 1/2 (544)
Built-in height with mains connection box in in.(mm)	3 (75)
Cutout dimensions in in. (width) with proud-mounted installation	34 1/2 (876)
Cutout dimensions in in. (depth) with proud-mounted installation	20 1/2 (518)
Weight in lbs. (kg)	41 (19)
Total connected load in kW	10.0
Power cord length in m	4 (1.4)
Standard accessories	
Razor-blade scraper	•
Connection wire	•



KM 5627 208V

Electric cooktop 36 1/8 (915) wide for extremely convenient cooking.







1. Front 2. Building-in depth 3. Flexible metal hose, L = 1200 mm

1/4" 217/16 215/16 36' (2) 21/8 Sr 3/16" 2 341/2 503<sup>/8</sup>" 1 2 5/8" 2 2 2 15/16" 2 161/8" 211 7/16 31 1 315/1e 83/16 201/16 3 34

KM 5627 (Installation drawing)

Front
Building-in depth
Flexible metal hose, L = 47 1/4"