



Art Cool™ Gallery Inverter

Benefits of Multi F Systems

- Individual zone control
- Maximum flexibility
- Operating ranges of 14°F to 118°F (DB) in cooling and 0°F to 64°F (WB) in heating
- Quiet and comfortable environment
- Safer and easier installation with reduced ductwork
- Cost efficient
- Lightweight and compact system components

Multi-Zone System Indoor Unit

Multi F multi-zone comfort solutions are air-conditioning systems that “split” into indoor and outdoor units, providing a smart alternative to both central HVAC and window-mounted air conditioners. These Inverter heat pump systems are available in a variety of configurations to suit different cooling and heating situations.

Multi F Art Cool™ Gallery Indoor Units

LG's Multi F Art Cool™ Gallery indoor units are designed to frame any 20" x 20" photograph, picture, or artwork of your choice. Installation is simple—the units mount securely on a vertical surface using screws. The removable, washable filter is easily accessible from the front of the unit without using tools. Each indoor unit includes its own wireless handheld remote controller; an LG-supplied wired controller is available separately.



MULTI F

Quiet, Custom Comfort

Motorized oscillating guide vanes allow control of airflow direction from side to side. A motorized air sweep louver can automatically change airflow by directing the air up and down for a uniform air distribution.

Choose from Low, Med, High, Power Cool and Auto settings in Cooling mode; Low, Med, High, Power Heat and Auto settings in Heating mode. The Auto setting adjusts fan speed based on the difference between the controller setting and the room temperature. Also, a Chaos setting simultaneously and randomly changes fan speed and airflow direction, simulating a natural outdoor breeze. And Art Cool™ Gallery indoor units operate at sound levels no higher than 42 dB(A), contributing very little noise to the room.

Quality Commitment

LG is committed to the success of air-conditioning projects. We provide technical support during installation, and offer a variety of classes designed for installers and service providers. Classes are conducted at LG's training centers and in field locations at various times throughout the year and upon special request.



About LG Electronics, Inc.

LG Electronics, Inc. is a global leader and technology innovator in consumer electronics, mobile communications, and home appliances, employing more than 213,000 people in more than 60 countries worldwide. LG's commercial air conditioning business unit was established in 1968, and offers VRF, Multi F, duct-free split systems, packaged terminal air conditioners (PTACs), and room air conditioners.

With LG, it's all possible.™

Art Cool™ Gallery Inverter Multi F System Indoor Unit

LMAN097HVP

9,000 Btu/h Nominal Cooling Capacity
10,400 Btu/h Nominal Heating Capacity

LMAN127HVP

11,200 Btu/h Nominal Cooling Capacity
13,300 Btu/h Nominal Heating Capacity



LMAN097-127HVP



Features

- Inverter (Variable speed fan)
- Chaos swing
- Jet Cool
- Jet Heat
- Self-cleaning indoor coil
- Auto operation
- Auto restart operation
- 24-Hour on-off timer
- Includes wireless LCD remote controller, batteries, holder and holder hardware; wired controller available as an option

Warranty: Five (5) years parts.

Model Number	LMAN097HVP	LMAN127HVP
Nominal Cooling Capacity (Btu/h)	9,000	11,200
Nominal Heating Capacity (Btu/h)	10,400	13,300
Fan		
Type	Turbo	Turbo
Motor Output (W) x Qty.	24 x 1	24 x 1
Motor/Drive	Brushless Digitally Controlled / Direct	Brushless Digitally Controlled / Direct
Airflow Rate (H/M/L) (CFM)	272 / 208 / 155	314 / 258 / 198
Unit Data		
Refrigerant Type / Control	R410A / EEV	R410A / EEV
Power Supply (Phase / V / Hz)	1 / 208-230 / 60	1 / 208-230 / 60
Rated Amps (A)	0.2	0.2
Sound Pressure Level ±3 dB(A) (H/M/L)	39 / 35 / 31	42 / 38 / 34
Dimensions (W x H x D, in.)	23-5/8 x 23-5/8 x 5-25/32	23-5/8 x 23-5/8 x 5-25/32
Net Unit Weight (lbs.)	32	32
Shipping Weight (lbs.)	37	37
Power Wiring / Communications Cable (No. x AWG)	4 x 18	4 x 18
Heat Exchanger (Row x Column x Fin / inch) x Number	(2 x 20 x 21) x 1	(2 x 20 x 21) x 1
Piping		
Liquid (in.)	1/4	1/4
Vapor (in.)	3/8	3/8
Drain O.D. / I.D. (in.)	27/32 / 5/8	27/32 / 5/8