

G 7156 SCVi

Fully integrated dishwasher XXL
with 3D MultiFlex Tray for maximum convenience.



- Perfect results in less than one hour - QuickIntense Wash
- Everything completely dry – AutoOpen drying
- Very easy door opening and closing – ComfortClose
- Versatile and secure – ExtraComfort basket design

EAN: 4002516261452 / material number: 11387590

Construction type	
Fully integrated dishwashers	•
24 inch dishwasher	•
Full size dishwasher	•
Design	
Fascia color	Stainless Steel.
Fascia panel version	Fully integrated fascia
Control type	Programme selector button
Control panel	1-line text display
Display color	White
MultiLingua	•
Convenience	
Door closing aid	ComfortClose
Operating noise in dB(A)	43
Countdown indicator	•
Delay start up to 24 hours	•
In-operation indication	Display
Display language selection	•
Efficiency and sustainability	
Water consumption in the sensor wash program in gal(l) from	6.4
EcoFeedback	•
EcoPower Technology	•
Hot water connection	•
Half load	•
Gentle on dishware/glass	
AutoOpen drying	•
SensorDry	•
Active condensation drying	•
Perfect GlassCare	•
Dishwashing programs	
Normal	•
Pots & Pans	•
QuickIntenseWash	•
SaniWash	•
Rinse & Hold	•
Rinse options	
IntenseZone	•
Express	•
Extra Clean	•
Extra Dry	•
Basket design	
Cutlery loading	3D MultiFlex tray
FlexCare glass holder	2
FlexCare cup rack	1
Basket design	ExtraComfort
Safety	
Waterproof system	•
Check filter saturation indicator	•
Child Safety lock	•

More information at www.MieleUSA.com

For further information please see next page...

G 7156 SCVi

Fully integrated dishwasher XXL
with 3D MultiFlex Tray for maximum convenience.



Technical data	
Appliance width in in.(mm)	23 5/8 (598)
Appliance height in in.(mm)	33 3/8 (845)
Appliance depth in in.(mm)	22 1/2 (570)
Appliance depth with door open in in.(cm)	47 1/2 (120.5)
Net weight in lbs. (kg)	106 (48.0)
Total connected load in kW	1.4
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Length of water inlet hose in ft (m)	4 (1.50)
Length of water drain hose in ft (m)	4 (1.50)
Length of electrical wire in ft (m)	3 (1.20)
Min. – max. front panel weight in lb (kg)	4.0
[can be retrofitted by Technical Service]	7.0