

Your All-in-One Dual Answer for Cooling and Heating

Climate Pro D12e heat pumps let you heat or cool for year-round comfort. No costly installation is needed, simply roll it in, set it up, and turn it on.

Key Features

- Cooling capacity of 11,450 Btu/h and heating capacity of 9,900 Btu/h for versatility and comfort.
- Compact footprint for space-limited applications.
- Made with safety in mind — no hot-to-the-touch surfaces.
- Effective moisture removal — hastens drying for humid and water-damaged areas.
- Excellent back-up protection for sensitive electronics.
- Connectivity ready with remote monitoring, geolocation and performance notifications.*

*Subscription required. See your local dealer for details.



Ideal for . . .

Offices
Conference Rooms
Schools
Hospitals
Retail Spaces
Warehouses
Assembly Lines
Emergency Back-up
Off-season Spot Cooling and Heating
Supplemental Cooling and Heating

Another line of quality products by DENSO.

DENSO

MovinCool is a brand of DENSO Corporation, the world's largest manufacturer of spot air conditioners. MovinCool spot air conditioners and heat pumps are backed by a full three-year on-site parts and labor warranty with registration—the strongest in the industry.



Climate Pro® D12e Specifications

D12e		
Electronic Features	Control Panel	Programmable
Cooling/Heating Capacity Rating Conditions	Cooling: 95°F @ 60% RH Heating: Indoor @ 70°F / Outdoor @ 47°F @ 50% RH	Cooling: 11,450 Btu/h Heating: 9,900 Btu/h
Energy Efficiency Ratio (EER)		Cooling: 9.4 Heating: 9.5
Electrical Characteristics	Voltage Requirement (60 Hz)	1 Phase, 115 V
	Total Power Consumption	Cooling: 1.20 kW Heating: 1.10 kW
	Current Consumption	Cooling: 10.9 amps Heating: 9.3 amps
	Recommended Fuse Size	15 amps
	NEMA Plug Configuration	5-15P
	Min. – Max. Voltage	104 – 127 V
Fan Motor Output	Evaporator	0.06 kW
	Condenser	0.12 kW
Indoor Heat Exchanger (Supply)	Fan Type	Centrifugal
	Max. Air Flow - High/Mid/Low	420 / 340 / 280 CFM
	Max. External Static Pressure	0.31 IWG
Outdoor Heat Exchanger (Exhaust)	Fan Type	Centrifugal
	Max. Air Flow	760 CFM
	Max. External Static Pressure	0.19 IWG
Compressor	Type	Hermetic Rotary
	Output	0.7 kW
Refrigerant	Type	R-32
	Amount	1.17 lb
Dimensions	W x D x H	22 x 27 x 47 in
Net Weight/Shipping Weight		186 / 221 lb
Power Cord	Gauge	14 AWG (3-core)
	Length	10 ft
Condensate Tank Capacity (approx.)		5 gal
Operating Conditions	Min. – Max. @ 50% RH	Cooling: 65° – 95°F
		Heating without Plenum: 40° – 80°F (air entering indoor and outdoor heat exchangers) Heating with Plenum: 40° – 80°F (air entering indoor heat exchanger) 24° – 80°F (air entering outdoor heat exchanger)
Max. Equivalent Duct Length	Supply Duct Hose	30 ft
	Exhaust Duct Hose	100 ft
Max. Sound Level (high/mid/low)	With Condenser Duct	62 / 61 / 60 dB(A)
	Without Exhaust Duct	62 / 61 / 60 dB(A)

*All specifications subject to change without notice. All models come with a standard warranty covering the entire unit and compressor for 12 months. Visit MovinCool.com/warranty for details on MovinCool's industry-best free Extended Warranty Program which includes three (3) years for both parts and labor on portable units.

DENSO Products and Services Americas, Inc.
3900 Via Oro Avenue | Long Beach CA 90810 USA
+1-800-264-9573 | MovinCool.com

