



Your All-in-One Dual Answer for Cooling and Heating

Climate Pro D18e heat pumps let you heat or cool for year-round comfort. No costly installation is needed, simply roll it in, set it up, and turn it on.

Key Features

- Cooling capacity of 16,300 Btu/h and heating capacity of 13,100 Btu/h for versatility and comfort.
- Compact footprint for space-limited applications.
- Made with safety in mind — no hot-to-the-touch surfaces.
- Effective moisture removal — hastens drying for humid and water-damaged areas.
- Excellent back-up protection for sensitive electronics.
- Connectivity ready with remote monitoring, geolocation and performance notifications.*

*Subscription required. See your local dealer for details.



Ideal for . . .

Offices
Conference Rooms
Schools
Hospitals
Retail Spaces
Warehouses
Assembly Lines
Emergency Back-up
Off-season Spot Cooling and Heating
Supplemental Cooling and Heating

Another line of quality products by DENSO.

DENSO

MovinCool is a brand of DENSO Corporation, the world's largest manufacturer of spot air conditioners. MovinCool spot air conditioners and heat pumps are backed by a full three-year on-site parts and labor warranty with registration— the strongest in the industry.



D18e			
Electronic Features	Control Panel		Programmable
Cooling/Heating Capacity Rating Conditions	Cooling: 95°F @ 60% RH	Heating: Indoor @ 70°F / Outdoor @ 47°F @ 50% RH	Cooling: 16,300 Btu/h Heating: 13,100 Btu/h
Energy Efficiency Ratio (EER)		Cooling: 10.4	Heating: 10
Electrical Characteristics	Voltage Requirement (60 Hz)	1 Phase, 115 V	
	Total Power Consumption	Cooling: 1.56 kW	Heating: 1.31 kW
	Current Consumption	Cooling: 13.8 amp	Heating: 11.7 amps
	Recommended Fuse Size	20 amps	
	NEMA Plug Configuration	5-20P	
	Min. – Max. Voltage	104 – 127 V	
Fan Motor Output	Evaporator	0.06 kW	
	Condenser	0.12 kW	
Indoor Heat Exchanger (Supply)	Fan Type	Centrifugal	
	Max. Air Flow - High/Mid/Low	510 / 440 / 350 CFM	
	Max. External Static Pressure	0.31 IWG	
Outdoor Heat Exchanger (Exhaust)	Fan Type	Centrifugal	
	Max. Air Flow	825 CFM	
	Max. External Static Pressure	0.19 IWG	
Compressor	Type	Hermetic Rotary	
	Output	0.9 kW	
Refrigerant	Type	R-32	
	Amount	1.72 lb	
Dimensions	W x D x H	22 x 27 x 51 in	
Net Weight/Shipping Weight		195 / 234 lb	
Power Cord	Gauge	12 AWG (3-core)	
	Length	10 ft	
Condensate Tank Capacity (approx.)		5 gal	
Operating Conditions	Min. – Max. @ 50% RH	Cooling: 65° – 95°F	
		Heating without Plenum: 40° – 80°F (air entering indoor and outdoor heat exchangers)	Heating with Plenum: 40° – 80°F (air entering indoor heat exchanger) 24° – 80°F (air entering outdoor heat exchanger)
Max. Equivalent Duct Length	Supply Duct Hose	25 ft	
	Exhaust Duct Hose	100 ft	
Max. Sound Level (high/mid/low)	With Condenser Duct	66 / 65 / 64 dB(A)	
	Without Exhaust Duct	66 / 65 / 64 dB(A)	

*All specifications subject to change without notice. All models come with a standard warranty covering the entire unit and compressor for 12 months. Visit MovinCool.com/ warranty for details on MovinCool's industry-best free Extended Warranty Program which includes three (3) years for both parts and labor on portable units.

DENSO Products and Services Americas, Inc.
 3900 Via Oro Avenue | Long Beach CA 90810 USA
 +1-800-264-9573 | MovinCool.com

